

Internal Hardwood Doors



DIC65** Worcester Oak Glazed



Dimensions		
Door Width	2'6"	2'9"
Product Code	DIC6560	DIC6570
Building Regulations		M
Weights (kg)	24.8	26.2
Dim A (mm)	762	838
Dim B (mm)	522	598
Dim C (mm)	120	120
Dim D (mm)	1981	1981
Dim E (mm)	175	175
Dim F (mm)	110	110

All sizes subject to standard industry tolerances

Part M Doors (M) - Mobility and Access



HOWDENS JOINERY CO.

MAKING SPACE MORE VALUABLE

Internal Hardwood Doors

General Construction

The distinctive glazed panels of this door are perfectly suited to allow optimum levels of light to pass from room to room.

Construction

Dowels joint and assembled using glue.
Made of veneered particleboard & wooden lipping.
0.6mm American White Oak Veneer.
Pre Glazed with a 4mm clear toughened glass.

Timber Specification

Timber Species	Kembang Semangkok (KSK)
Moisture Content	10 - 14%

Lipping

10mm hardwood (KSK) lippings applied on each vertical stile

Maximum Trim

If the door is to be reduced in size, an equal amount of timber should be cut down from either side/top or bottom (please note that this must never exceed 10mm in total, 5mm each side).

Fire Certificate: Not Applicable

Glazing Certificate: Available on Request

