

Sentry Solid Core Blank Lightweight



Construction	
Construction material	Engineered timber construction
Material core	Albasia Falcata
Veneer thickness	3.6 mm
Country of origin	Various
Lock block additional information	A lock block is not included on this door as it is a solid construction. The lock can be fitted in any location on either side.

Edging Information		
	Lipping dimensions	Maximum trim
Edging additional information	Door can be trimmed to size. Please refer to the Fire Certificate	



Dimensions						
Product code	Product height	Product width	Product thickness	Product weight	Fire rating	Building regulations
DXF0046 Regional	7'0" / 2135mm	3'0" / 915mm	44mm	30kg	FD30	M
DXF0047 Regional	7'0" / 2134mm	3'0" / 914mm	54mm	49.92kg	FD60	M
DXF0048 Regional	8'0" / 2439mm	4'0" / 1,219mm	44mm	45kg	FD30	M

Key information

All sizes subject to standard industry tolerances

M = Part M - Mobility and access*

L = Part L - Warmth & insulation suitable for new build*

L = Part L - Warmth & insulation suitable for refurbishment projects*

E = Part E - Reduction of sound travel*

FD30/60/120 = Certified fire door*

F = Forest Stewardship Council (FSC®)*

P = Programme for the Endorsement of Forest Certification schemes (PEFC™)*

UK = UK Manufactured

† = Subject to availability

*Not applicable to all doors, please see the Dimensions table above for products that meet these standards

