

Metro Smooth



Construction	
Construction material	Softwood timber stiles and rails
Material core	Flaxboard
Country of origin	UK
Lock block additional information	A lock block is not included on this door as it is a solid construction. The lock can be fitted in any location on either side, avoiding mid rail joints as this can weaken the structure of the door.

Edging Information		
	Lipping dimensions	Maximum trim
Top		0 mm
Bottom		6 mm
Each side		4 mm
Edging additional information	An equal amount of timber should be removed from each side & bottom. Remaining within the parameters of the maximum trim instructions ensures the construction of the door is not compromised and that the door when fitted complies with the fire certificate.	

Fitting and finishing

All fire doors must be fitted in accordance with the fire certificate. Doors must be sealed on all edges prior to installation. Please note: Coat hooks cannot be fitted to all doors. Refer to fitting information.

Please refer to door instructions for all fitting information.

Ready for priming and painting

Fire certification available



Dimensions								
Product code	Product height	Product width	Product thickness	Product weight	Fire rating	Building regulations	Top rail	Bottom rail
DFM2240 NEW UK	6'6" / 1981mm	2'3" / 686mm	44mm	27.305kg	FD30	E	110mm	185mm
DFM2260 NEW UK	6'6" / 1981mm	2'6" / 762mm	44mm	28.826kg	FD30	E	110mm	185mm
DFM2270 NEW UK	6'6" / 1981mm	2'9" / 838mm	44mm	31.603kg	FD30	E M	110mm	185mm

Key information

All sizes subject to standard industry tolerances

M = Part M - Mobility and access*

L = Part L - Warmth & insulation suitable for new build*

L = Part L - Warmth & insulation suitable for refurbishment projects*

E = Part E - Reduction of sound travel*

FD30/60/120 = Certified fire door*

F = Forest Stewardship Council (FSC®)*

P = Programme for the Endorsement of Forest Certification schemes (PEFC™)*

UK = UK Manufactured

† = Subject to availability

*Not applicable to all doors, please see the Dimensions table above for products that meet these standards

