

# Hob & Drawer Fitting Matrix



# Hotpoint

## Hob & Drawer Fitting Matrix

Hobs	SKU	Appliance Description	Hob Depth mm	Minimum Clearance Specified (mm) + 6mm Shield	Blum Drawer										Standard Drawer										Internal drawer in 2 draw base cab									
					Standard					Balham					Standard					Balham					Standard					Balham				
					60mm					90mm					40mm					70mm					30mm					60mm				
					38mm	28mm	22mm	20mm	12mm	38mm	28mm	22mm	20mm	12mm	38mm	28mm	22mm	20mm	12mm	38mm	28mm	22mm	20mm	12mm	38mm	28mm	22mm	20mm	12mm	38mm	28mm	22mm	20mm	12mm
	HHP1800	65cm 4 Zone flex induction	53	26	19	9	3	1	-7	49	39	33	31	23	-1	-11	-17	-19	-27	29	19	13	11	3	-11	-21	-27	-29	-37	19	9	3	1	-7
	HHP1801	80cm 5 Zone flex induction	53	26	19	9	3	1	-7	49	39	33	31	23	-1	-11	-17	-19	-27	29	19	13	11	3	-11	-21	-27	-29	-37	19	9	3	1	-7
	HHP1100	4 burner gas hob SS	41	26	30	20	14	12	4	60	50	44	42	34	10	0	-6	-8	-16	40	30	24	22	14	0	-10	-16	-18	-26	30	20	14	12	4
	HHP1101	5 burner Gas hob SS	41	26	30	20	14	12	4	60	50	44	42	34	10	0	-6	-8	-16	40	30	24	22	14	0	-10	-16	-18	-26	30	20	14	12	4

- Compatible
- Use LEAFMDBBHM guide at 125mm runner position
- Not Compatible

Noted value is gap between base of separator plate and top of drawer

All Dims are in mm

All hobs do not include putty, foam or worktop sealant

All hobs positioned in line with fitting instructions

Heat shield thickness set at 6mm

<2mm classed as 'not fitting' due to tolerances of cabinets could result in clashes