

Pre-finished Dordogne Oak- Fire



Construction	
Construction	Slab
Door construction information	Solid Core Slab Construction
Lock block additional information	A lock block is not included on this door as it is a solid construction. The lock can be fitted in any location on either side.

Fire certification available

Edging Information	
	Maximum trim
Top	0 mm
Bottom	5 mm
Each side	5 mm

Dimensions						
Product code	Product height	Product width	Product thickness	Product weight	Building regulations	Top rail
DFH7040	6'6" / 1981mm	2'3" / 686mm	44mm	42kg		117mm
DFH7060	6'6" / 1981mm	2'6" / 762mm	44mm	46kg		117mm
DFH7070	6'6" / 1981mm	2'9" / 838mm	44mm	51kg	M	117mm

Key information

All sizes subject to standard industry tolerances

M = Part M - Mobility and access*

L = Part L - Warmth & insulation suitable for new build*

L = Part L - Warmth & insulation suitable for refurbishment projects*

E = Part E - Reduction of sound travel*

FD30/60/120 = Certified fire door*

F = Forest Stewardship Council (FSC®)*

P = Programme for the Endorsement of Forest Certification schemes (PEFC™)*

UK = UK Manufactured

† = Subject to availability

*Not applicable to all doors, please see the Dimensions table above for products that meet these standards