



Construction Products Regulation (EU) No 305/2011 (CPR)

Declaration of Performance

Declaration number: HJ-022-HC

Product identification: HJ All in One Adhesive and Sealant Clear

Other identifying element(s): See Page 2

Intended use: Part 1: Sealants for façade elements for interior applications only

Notified Body: SKZ Notified Body No. 1213

AVCP System: System 4 (System 3 for reaction to fire)

Declared Performance:

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	Class E	EN15651-1:2012
Release of chemicals dangerous to the environment and health	NPD (*)	
Water tightness and air tightness		
Resistance to flow	≤ 3 mm	
Loss of Volume	≤ 45%	
Tensile properties: elongation at break at 23 °C	≥ 25%	
Durability	Pass	

(*) See material safety data sheet

NPD: No performance determined

The performance of the product identified above is in conformity with the declared performance.

Signed for and on behalf of the manufacturer by:



LAMONA
Exclusive to Howdens Joinery Co.

Howdens Joinery Group Plc.
40 Portman Square
London
W1H 6LT
www.howdens.com

Linzi Walker
Director of Appliances, Joinery & Hardware Category
08th September 2020

Howdens Joinery
The Grove
Brackmills Industrial Estate
Lilliput Road
Northampton
NN4 7EY
UK



Construction Products Regulation (EU) No 305/2011 (CPR)

Declaration of Performance

Declaration number: HJ-022-HC

Product identification: HJ All in One Adhesive and Sealant Clear

Other identifying element(s): GAR0550



LAMONA

Exclusive to Howdens Joinery Co.

Howdens Joinery Group Plc.
40 Portman Square
London
W1H 6LT
www.howdens.com



Construction Products Regulation (EU) No 305/2011 (CPR)

Declaration of Performance

Declaration number: HJ-022-HC

Product identification: HJ All in One Adhesive and Sealant Clear

Other identifying element(s): See Page 2

Intended use: Part 1: Sealants for façade elements for interior applications only

Notified Body: SKZ Notified Body No. 1213

AVCP System: System 4 (System 3 for reaction to fire)

Declared Performance:

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	Class E	
Release of chemicals dangerous to the environment and health	NPD (*)	EN15651-1:2012
Water tightness and air tightness		
Resistance to flow	≤ 3 mm	
Loss of Volume	≤ 45%	
Tensile properties: elongation at break at 23 °C	≥ 25%	
Durability	Pass	

(*) See material safety data sheet
NPD: No performance determined

The performance of the product identified above is in conformity with the declared performance.

Signed for and on behalf of the manufacturer by:

Linzi Walker
Director of Appliances, Joinery & Hardware Category
08th September 2020

Howdens Joinery
The Grove
Brackmills Industrial Estate
Lilliput Road
Northampton
NN4 7EY
UK



Exclusive to Howdens Joinery Co.

Howdens Joinery Group Plc.
40 Portman Square
London
W1H 6LT
www.howdens.com