

Declaration of Performance

Declaration number: HJ-023-HC

Product identification: HJ All in One Adhesive and Sealant Colours

Other identifying element(s): See Page 4

Intended use: Sealant for non-structural use in joints in

buildings and pedestrian walkways
Part 1: Sealants for façade elements
Part 3: Sealants for Sanitary elements
Part 4: Sealants for pedestrian walkways

EN1565-1: F-EXT-INT-CC (CLASS 25HM)

EN1565-3: S (CLASS XS3)

EN1565-4: PW-EXT-INT-CC (CLASS 25HM)

Notified Body: SKZ Notified Body No. 1213

AVCP System: System 3 (System 3 for reaction to fire)

Declared Performance:

Conditioning: Procedure B (according to ISO 8340)
Substrate: Mortar M1 (with primer P03)

Glass (without primer)

Anodised aluminium (without primer)

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	Class E	
Release of chemical dangerous to	NPD (*)	
the environment and health	NPD (")	
Water tightness and air tigh		
Resistance to flow	≤ 3 mm	
Loss of volume	≤ 10%	
Tensile Properties at maintained	NF	EN15651-1:2012
extension after water immersion	INF	
Tensile Properties (secant modulus)	NR	
for use in cold climate areas (-30°C)	INIX	
Tensile Properties at maintained		
extension for use in cold climate	NF	
areas (-30°C)		
Durability	Pass	





Howdens Joinery Group Plc. 40 Portman Square London W1H 6LT www.howdens.com (*) See material safety data sheet NPD: No performance determined

NF: No failure NR: Not required



Declaration of Performance

Declaration number: HJ-023-HC

Product identification: HJ All in One Adhesive and Sealant Colours

Declared Performance:

Substrate: Glass (without primer)

Anodised aluminium (without primer)

Harmonised

Essential Characteristics	Performance	Harmonised Technical	
		Specification	
Reaction to fire	Class E		
Release of chemical dangerous to	NPD (*)		
the environment and health	NI D ()		
Water tightness and air			
Vertical flow resistance	≤ 3 mm	EN15651-3:2012	
Loss of volume	≤ 20%		
Tensile Properties at maintained	NF		
extension after water immersion	INF		
Microbiological growth	3		
Durability	Pass		

Substrate: Mortar M1 (with primer P03)

Essential Characteristics	Performance	Technical Specification
Reaction to fire	Class E	
Release of chemical dangerous to the environment and health	NPD (*)	
Water tightness and air	tightness	
Tensile Properties at maintained extension	NF	
Loss of volume	≤ 10%	
Tear resistance	NF	
Adhesion / cohesion properties at maintained extension after 28 days water immersion	NF / change of secant modulus ≤ 50%	EN15651-4:2012
Adhesion / cohesion properties at maintained extension after 28 days saltwater immersion	NF	
Tensile properties (secant modulus) for use in cold climate areas (-30 ° C)	NR	
Tensile properties at maintained extension for use in cold climate areas (-30 °C)	NF	
Durability	Pass	



Howdens Joinery Group Plc. 40 Portman Square London W1H 6LT www.howdens.com (*) See material safety data sheet NPD: No performance determined

NF: No failure NR: Not required



Declaration of Performance

Declaration number: HJ-023-HC

Product identification: HJ All in One Adhesive and Sealant Colours

The performance of the product identified above is in conformity with the declared performance.

Signed for and on behalf of the manufacturer by:

Linzi Walker

Director of Appliances, Joinery & Hardware Category

1 healkes

08th September 2020

Howdens Joinery
The Grove
Brackmills Industrial Estate
Lilliput Road
Northampton
NN4 7EY
UK



Exclusive to Howdens Joinery Co.

Howdens Joinery Group Plc. 40 Portman Square London W1H 6LT www.howdens.com



Declaration of Performance

Declaration number: HJ-023-HC

Product identification: HJ All in One Adhesive and Sealant Colours

Other identifying element(s):

GAR0551, GAR0552, GAR0553, GAR0554



Howdens Joinery Group Plc. 40 Portman Square London W1H 6LT www.howdens.com