



Internal Pre-Finished Flush Veneer FD30 Fire Door

Installation, Finishing & Care Instructions

Important Notes

It is important you read this leaflet before installing the door. The guidelines below will help ensure the door is fitted correctly and in a suitable environment. **Failure to adhere to the instructions could invalidate any warranty claims.**

- **Doors must be stored flat on 3 level bearers**
- **Doors must be kept dry at all times**
- **Avoid direct contact with sunlight**
- **Do not install or store the door in newly plastered rooms**
- **Polythene wrapping should remain on the doors until immediately before installation**
- **Check the door for defects and damage before installation, do not install the door if any defects or damage are found**
- **Any door which has been worked on cannot be exchanged, with the exception of a door with a proven manufacturing defect**
- **Doors should be handled carefully with clean gloves and not dragged across each other or other surfaces**
- **Any trimmed edges and all cut outs must be re-finished before hanging**

IT IS ESSENTIAL THAT THIS DOOR IS INSTALLED USING THE FRAME, INTUMESCENTS AND IRONMONGERY DETAILED IN THE TEST EVIDENCE, ASSESSMENT OR CERTIFICATION. ANY DEVIATION FROM THIS WILL RESULT IN THE CERTIFICATION BEING INVALID AND THE DOOR NOT PERFORMING AS IT SHOULD IN THE EVENT OF A FIRE

Finishing

Both faces and all edges of this door are lacquered. To reduce the risk of distortion all trimmed edges and cut outs must be re-finished before the door is hung.

You can use water based or solvent varnishes. If using a solvent based finish, we recommend the use of a VOC 2010 compliant product.

Hanging

Note: Doors for internal use should be fully finished before being hung. The below covers doors hung as single doors only. This range of Fire Doors are tested to EN1634-1 and are FD-30 Fire Rated when installed into the appropriate frame of 70 x 30mm min thickness section and with a min of 12mm deep rebate or planted stop (see diagram 2 overleaf). If using planted stops, they must be fixed using glue and 40mm long steel pins. 15x4mm Lorient type 617 Intumescent strips must be fitted into the jambs and head of the frame.

It is the responsibility of the installer to ensure that all Certifire hardware, Intumescent strips, door and frame are fitted correctly to meet all current Building and Fire Regulations.

If in doubt check with your local Building Control Officer.

Do not plane the door unless absolutely necessary, and if so, do not remove any more than 3mm from the sides or bottom of the door. Do not trim the top edge or remove the Certifire label.

When hanging the Door there should be a 2mm min to 4mm max gap at each side and top (see dimension A & B diagram 2) and a maximum gap of 8mm between the bottom of the Door and the floor covering, (see dimension C diagram 2). A minimum of three cut-outs are required in the Door stiles and frame jamb for the hinge position (See diagram 1 overleaf). Using the hinge as a template, mark the hinge positions on the appropriate Door stile. Then position the Door in the Frame and transfer the markings from the Door onto the Frame, ensuring that they are perfectly aligned. Hinges must be CE marked for use with fire resisting doors.

Again, using the hinge as a template, mark the hinge position and cut-out the recesses in the door and frame to the required depth allowing for any intumescent protection. Pilot holes should always be drilled for the screws.

Fit the hinges to the Door in the prepared cut-outs with the screws supplied, fully fitting screws into all the holes in the hinge plate.

Hang the door into the Frame, supporting it to achieve the correct alignment. Initially insert only one screw per hinge plate.

Check that the Door closes correctly and has the height and width clearances as in diagram 2 below. If the Door touches the Frame at any point, the hinge housings may need adjustment. When the alignment is correct, fit the remaining screws into the hinges. If required, fit Door Stops to the frame.

For further information (including other configurations) please refer to Certifire Certificate CF5740

'IF IN DOUBT SHOUT'

If you have any queries relating to the installation of this Fire Door, contact your local depot

Maintenance & Repairs

The surface finish will be highly resistant to the rigours of normal use and should usually only need regular light dusting with a soft cloth.

If sticky marks occur on the surface they can be removed with a dilute solution of warm soapy water. The offending area should be rubbed lightly and then completely dried immediately afterwards.

Use of cleaning materials containing abrasive compounds, solvents, acidic or caustic substances and any bleaches containing oxidising substances should be avoided as prolonged use may damage the painted surface.


As a general recommendation furniture polishes containing silicones should be avoided as they can contaminate the finish surface and cause problems if the finish ever needs repairing. If scratches or blemishes in the paint surface require repairing use Howdens repair kit.

FIRE DOORS SHOULD BE ROUTINELY CHECKED EVERY 6 MONTHS TO THE CRITERIA IN THE CHECKLIST BELOW

Conditions of Sale


Howdens will not be held responsible for any incidental work or problems as a result of bad storage, handling or incorrect fitting and finishing of our doors. The foregoing does not affect your statutory rights.

Diagram 1 - Hinge Positions



Note: Door design shown is for illustration purposes only

Diagram 2 - Minimum Frame Dimensions



Fire Door Checklist - complete and give to the client

CORRECT INSTALLATION CHECKLIST - REFER TO "CERTIFIRE CERTIFICATE CF5740 FOR DETAILS

(Certificates available at your local depot)

- Frame to wall gaps / packing / gap sealant
- Hinge positions and no missing screws
- Door to frame and threshold gaps
- Intumescent / smoke seals in position, allow door to shut and fill all gaps (smoke seals)

- Latches and locks engage / release
- Closer suitably closes door from any angle
- Appropriate signage fixed to door or frame (e.g. Fire Door Keep Shut)

Client name:

Door SKU code:

Installed by:

Signed:

Date: