

4 Zone Bridging Induction Hob



Dimensions & packaging	
Product dimensions metric	H44mm x W590mm x D520mm
Product weight	11.389kg
Product packed dimension	H118mm x W678mm x D600mm
Product packed weight	12.3kg

Technical Information	
Power boost function	Power Boost Function
Timer	Yes
Residual heat indicator	Yes
Childlock facility	Yes
Fast fit clips	Includes Fast Fit Clips
Electrical supply voltage @ Frequency	220 - 240 V @ 50/60 Hz
Amperage required	32 A
Burner / Zone Power Range	1.8 to 2.8 kW
Fuel type	Electric
Safety cut out facility	Automatic Safety Shut Off
Induction Zone	Bridging
Wiring requirement	Hard Wired
Power boost function	Power Boost Function
Hobs Power Levels	14
Control type	Shift
Location of control panel	Front
Frameless hob	Frameless Hob
Keep warm function	Keep Warm Setting
Minimum worktop thickness	28 mm
Maximum input power (watts)	7,350 W
Mains lead length	1.5 m
Approval directives	CE RoHS UL (EU) EMC DEMKO WEEE LVD
Guarantee	3 Year Manufacturer's Guarantee

The company has a policy of continuous product development and reserves the right to change any products and specifications at any time.

Additional information

If installed over drawers, worktop thickness need only be 12mm minimum