

Hob & Drawer Fitting Matrix



ZANUSSI

Hob & Drawer Fitting Matrix

Hobs	SKU	Appliance Description	Hob Depth mm	Minimum Clearance Specified (mm) + 6mm Shield	Blum Drawer										Standard Drawer										Internal drawer in 2 draw base cab									
					Standard					Balham					Standard					Balham					Standard					Balham				
					60mm					90mm					40mm					70mm					30mm					60mm				
Worktop Thickness					38mm	28mm	22mm	20mm	12mm	38mm	28mm	22mm	20mm	12mm	38mm	28mm	22mm	20mm	12mm	38mm	28mm	22mm	20mm	12mm	38mm	28mm	22mm	20mm	12mm	38mm	28mm	22mm	20mm	12mm
	HZA1101	4 burner Gas Hob SS	45	5	42	32	26	24	16	72	62	56	54	46	22	12	6	4	-4	52	42	36	34	26	12	2	-4	-6	-14	42	32	26	24	16
	HZA1100	5 burner Gas Hob SS	40	5	47	37	31	29	21	77	67	61	59	51	27	17	11	9	1	57	47	41	39	31	17	7	1	-1	-9	47	37	31	29	21
	HZA1800	4 zone Induction Hob	55	15	22	12	6	4	-4	52	42	36	34	26	2	-8	-14	-16	-24	32	22	16	14	6	-8	-18	-24	-26	-34	22	12	6	4	-4
	HZA1850	4 zone Bridge Induction Hob	44	15	33	23	17	15	7	63	53	47	45	37	13	3	-3	-5	-13	43	33	27	25	17	3	-7	-13	-15	-23	33	23	17	15	7
	HZA1700	4 zone Ceramic Hob	50	15	27	17	11	9	1	57	47	41	39	31	7	-3	-9	-11	-19	37	27	21	19	11	-3	-13	-19	-21	-29	27	17	11	9	1

	Compatible
	Use LEAFMDBBHM guide at 125mm runner position
	Not Compatible

Noted value is gap between base of separator plate and top of drawer
 All Dims are in mm
 All hobs do not include putty, foam or worktop sealant
 All hobs positioned in line with fitting instructions
 Heat shield thickness set at 6mm
 <2mm classed as 'not fitting' due to tolerances of cabinets could result in clashes