

LAM2502 Lamona curved glass extractor



Technical Information	
Appliance energy efficiency	D
Extraction rate	428 m ³ /h
Extraction rate ltr/s	119 L/s
Noise level	56 dB
Number of fan speeds	3
Built in light	Built in lights
Number of lights	2x20 W Halogen
Control panel light	Yes
Grease filter	Washable grease filter
Outlet spigot diameter	150mm
Fitting guidelines - above worktop	750mm (700mm minimum)
Input - power motor maximum	100 W
Electrical supply rated voltage @ Frequency	220-240 V @ 50 Hz
Total input power (watts)	140 W
Supply needed	3 A
Mains lead	1.5 m
Accreditation CE	CE marked
Approval directives	LVD EMC WEEE RoHS
Guarantee	2 year guarantee

Dimensions & packaging	
Product dimensions metric	H534mm - H1000mm x W595mm x D500mm
Extractor Chimney dimensions	W323mm x D282mm

Accessories	
Rigid ducting kit 125mm	APL2805
Flexible ducting kit 125mm	APL2806
Flexible ducting kit 150mm	APL2807
Carbon Filter For Integrated / Conventional extractors	HJA2906

Additional information

Product dimensions include glass

Register 
my appliance



HOWDENS JOINERY CO. MAKING SPACE MORE VALUABLE

Issue Date: 8 December 2017 8:36 AM

The company has a policy of continuous product development and reserves the right to change any products and specifications at any time.