

Oak Effect Matt Laminate 28mm (600 Deep)



Technical Information	
Material	Chipboard
Worktop profile	Double Bullnose
Finish	Matt
Product radius	8 mm
Moisture resistance grade	P3
Worktop process	CPL
Accreditation general	BS 6222:1999 part 3 BS EN 312 (Board spec test - Domestic use compliance)
FIRA certification	FIRA Gold with P3 moisture resistance

Dimensions & Packaging	
Product dimensions metric	L3,000 mm x D600 mm x T28 mm
Product packed dimension	H28 mm x W3,043 mm x D600 mm

3m Length	UK F WKP1264
Edging Strip 1400mm	UK WKP1295
Jointing compound	UK WOR9042

Care & Installation	
<p>Care and maintenance</p>	<p>For general cleaning, use a damp cloth and a mild detergent or non-abrasive cleaner diluted in warm water. Abrasive scouring powders, creams and polishes should be avoided. Potentially persistent stains should be removed immediately. Buff the surface after cleaning with a soft cloth.</p> <p>Wipe spill liquid away from the worktop joints and cut-outs immediately.</p> <p>When applying the edging please ensure that it is lined up with the top of the worktop and overhangs at the bottom. Trim the edging at the bottom so that the trimmed edge is out of sight.</p>

Additional information

This worktop is suitable for use in bathrooms and kitchens as it holds a FIRA Gold Award and complies with BS EN 312: 2003 Type P3 for moisture resistance of chipboard substrate.



Key information

F = Forest Stewardship Council (FSC®)

P = Programme for the Endorsement of Forest Certification schemes (PEFC™)

UK = UK Manufactured



HOWDENS JOINERY CO. MAKING SPACE MORE VALUABLE

Issue Date: 16 December 2016 10:39 AM

The company has a policy of continuous product development and reserves the right to change any products and specifications at any time.