

Oak Effect Textured Laminate 38mm



Technical Information	
Material	Chipboard
Worktop profile	Double bullnose
Finish	Textured
Product radius	3 mm
Moisture resistance grade	P2
Worktop process	CPL
Light reflective value	26.7
Accreditation general	BS 6222:1999 part 3 BS EN 312 (Board spec test - Domestic use compliance)

Dimensions & packaging	
Product dimensions metric	L3,000mm x D616mm x T38mm
Product weight	41.46kg
Product packed dimension	H39mm x W3,043mm x D616mm
Product packed weight	41.72kg

Care & Installation	
Care and maintenance	<p>For general cleaning, use a damp cloth and a mild detergent or non-abrasive cleaner diluted in warm water. Abrasive scouring powders, creams and polishes should be avoided. Potentially persistent stains should be removed immediately. Buff the surface after cleaning with a soft cloth.</p> <p>Wipe spilt liquid away from the worktop joints and cut-outs immediately.</p> <p>When applying the edging please ensure that it is lined up with the top of the worktop and overhangs at the bottom. Trim the edging at the bottom so that the trimmed edge is out of sight.</p>

3m Length	UK F WKP7260
3.6m Length	UK F WKP7266
2.4m breakfast bar (950mm deep)	UK F WKP7285
Edging strip 1400mm	UK WKP7295
Jointing compound	UK WOR9042
Upstand 3m x 70mm x 20mm	UK P WKP0192
Backboard 3m x 600mm x 7mm	UK WKP7297
Backboard 1m x 750mm x 7mm	UK WKP7298



Key information

F = Forest Stewardship Council (FSC®)

P = Programme for the Endorsement of Forest Certification schemes (PEFC™)

UK = UK Manufactured



HOWDENS JOINERY CO. MAKING SPACE MORE VALUABLE

Issue Date: 22 June 2017 8:41 AM

The company has a policy of continuous product development and reserves the right to change any products and specifications at any time.