

# Grey Concrete Effect Square Edged-Laminate 22mm



Technical Information	
Material	Chipboard
Worktop profile	Square edged
Finish	Textured
Moisture resistance grade	P2
Worktop process	CPL
Max unsupported overhang for worktops / breakfast bar	300 mm
Accreditation general	BS 6222:1999 part 3 BS EN 312 (Board spec test - Domestic use compliance)

Dimensions & packaging	
Product dimensions metric	L3,000mm x D616mm x T22mm
Product weight	26.874kg
Product packed dimension	H24mm x W3,050mm x D616mm
Product packed weight	27kg

Products	
3m length	<b>UK F</b> WHT3760
2.4m breakfast bar (950mm deep)	<b>UK F</b> WHT3785
5m Edging strip	WHT3795
Jointing compound	<b>UK</b> WOR9029
Upstand 3m x 70mm x 20mm	<b>UK P</b> WHT3792
Matching backboards	<b>UK</b> WHT3797
Matching backboards	<b>UK</b> WHT3798

Care & Installation	
Care and maintenance	For general cleaning, use a damp cloth and a mild detergent or non-abrasive cleaner diluted in warm water Abrasives scouring powders, creams and polishes should be avoided. Potentially persistent stains should be removed immediately. Buff the surface after cleaning with a soft cloth Wipe spilt liquid away from the worktop joints and cut-outs immediately When applying the edging please ensure that it is lined up with the top of the worktop and overhangs at the bottom Trim the edging at the bottom so that the trimmed edge is out of sight

Additional information	
Support rails are required with certain cabinet configurations. Please check the support bar application document Slim worktop bolt - GIR0029 must be used when fitting the 22mm laminate worktop. This has a thinner profile to fit the worktop	



## Key information

**F** = Forest Stewardship Council (FSC®)

**P** = Programme for the Endorsement of Forest Certification schemes (PEFC™)

**UK** = UK Manufactured

