## Grey Oak Effect Square Edged Laminate 38mm



3m Length	<b>UK F</b> WKP0260
3.6m Length	<b>UK F</b> WKP0267
2.4m breakfast bar (950mm deep)	<b>UK F</b> WKP0285
Edging strip 5000mm	WKP0296
Jointing compound	UK WOR9033
Upstand 3m x 70mm x 20mm	<b>UK P</b> WKP0292
Backboard 3m x 600mm x 7mm	<b>UK</b> WKP0297
Backboard 1m x 750mm x 7mm	<b>UK</b> WKP0298

FSC www.fsc.org		
The mark of responsible fores	oty MANUF	ACTURED

## Key information

**F** = Forest Stewardship Council (FSC®)

**P** = Programme for the Endorsement of Forest Certification schemes (PEFC™)

**UK** = UK Manufactured



Technical Information	
Material	Chipboard
Worktop profile	Square edged
Finish	Textured
Moisture resistance grade	P2
Worktop process	CPL
Light reflective value	38.0
Accreditation general	BS 6222:1999 part 3 BS EN 312 (Board spec test - Domestic use compliance)

Dimensions & packaging	
Product dimensions metric	L3,000mm x D616mm x T38mm
Product weight	40.814kg
Product packed dimension	H40mm x W3,043mm x D616mm
Product packed weight	41.72kg

Care & Installation	
Care and	For general cleaning, use a damp cloth and a mild detergent or non-abrasive cleaner diluted in warm water
maintenance	Abrasive scouring powders, creams and polishes should be avoided. Potentially persistent stains should be removed
	immediately. Buff the surface after cleaning with a soft cloth
	Wipe spilt liquid away from the worktop joints and cut-outs immediately
	When applying the edging please ensure that it is lined up with the top of the worktop and overhangs at the bottom
	Trim the edging at the bottom so that the trimmed edge is out of sight