

# SOLUMASTIK

## Technical Description

Professional adhesive based on polyester resin and mastic.

## Characteristics

The product Solumastik® is formulated to cover all the adhesion and jointing requirements of Silestone® in all its varieties, with tailor-made colours for each one of the different varieties, with a common resin base in all of them. High sticking power.

## Application

The application is done manually over the pieces or other decorative elements to be adhered.

How to use:

- The surface must be dry and clean.
- Add hardener in a proportion of 2%.
- Mix homogeneously both components.
- Do not introduce mixing tools or other items with residues of hardener in the tin.
- Close the tin after every use.

## Working Properties

Dynamic Viscosity	24.000 – 28.000 cps (knife grade)
Gel time (20°C, 100gr. - DIN 1 6945)	4 - 5 min
Catalysis time (manipulation time)	20 - 30 min
Color	As per customer request



## Storage

Store away from sunlight between 15 °C and 25 °C (59°F - 77°F), in a dry and fresh place. Avoid contact between hardener and metal packages or other metallic items. Under these conditions, the shelf-life of the product is 12 months.

## Packaging

The product is available in 1,5 kg tins

## Safety

There are Safety Data Sheets available for customers. We highly advice you to follow handling, use, security and ecological instructions.

## Edition date

January, 2020