

619mm x 315mm x 68mm

OAKE & GRAY  
BEAUTIFUL FLOORING IN A SINGLE CLICK

RIGID LUXURY VINYL  
with underlay

#### IMPORTANT VINYL FLOORING FITTING NOTICE

- Fitting method for this product is unique and laying instructions must be followed. Store packs in a room with a minimum temperature of 20°C - 25°C.
- Do not open packs until you are ready to install the flooring and mix/shuffle panels from different packs when installing.
- Subfloor must be flat, smooth, clean, and dry. (Do not install in areas with high flooding risk such as saunas or outdoors).
- Use spacers to create the required expansion gap (6mm) around the edge of the room and all fixed objects including door frames, radiator pipes and cabinet legs.
- Do not install kitchen cabinets on top of the flooring.
- All joints should be tapped in to place using a rubber mallet and an off-cut piece of flooring (tapping block). No gaps should be visible.
- Ensure each row is checked for straightness before starting the following row.
- Short joints should be a minimum of 200mm apart from the short-end joint on the previous row.
- Use a straight edge to score the plank several times (decor facing upwards) then snap for a clean break.

#### PRE-INSTALLATION

**CHECK SUB-FLOOR MOISTURE CONTENT**

MINERAL BASED	TIMBER BASED
✓ DPM Always install a DPM where there are concerns over moisture content in the sub-floor ✓ CONCRETE ✓ GEBEST SKELETS ✓ MORTAR	✓ 8 - 12% moisture content ✓ DPM Breathable moisture barrier (a 300mm moisture barrier paper can be used) ✓ FLOORBOARDS ✓ CHIPBOARD ✓ PLYWOOD

**CLEAN THE SUB-FLOOR**

✓ SMOOTH  
✓ CLEAN  
✓ DRY  
✓ SOUND

**UNDERFLOOR HEATING**

Water and electric\* systems can be used

GRADUALLY INCREASE THE TEMPERATURE BY 5° PER DAY UP TO A MAX OF 30°

SEEK ADVICE FROM UNDERFLOOR HEATING MANUFACTURER

\*Electric systems must be encased in a minimum of 12mm of levelling compound above the pipes.

#### INSTALLATION (not suitable for external installation)

**TOOLS REQUIRED**

**1 CHOOSE DIRECTION OF INSTALLATION**

Calculate the room surface prior to installation. Plan for an extra 5 - 10% for waste.

**2 FIRST ROW**

Adjust width of first row if the width of the last row measures less than 50mm

**3 LAY FIRST ROW - engage end joints**

Work left to right

**4 USE SPACERS AROUND EDGE**

**5 MEASURE AND CUT**

Note: Use a straight edge to cut the plank several times (with decor facing upwards) then snap for a clean break

**6 CHECK ROW IS STRAIGHT**

**7 USE OFF-CUT FOR NEXT ROW**

>300mm  
30°

**8 FULLY ENGAGED PANEL JOINTS**

Use flooring off-cut to top on the long side

**9 FIT NEXT PANEL**

Fit into long edge, then slide along and drop down

30°

**10 REPEAT FOR ALL PANELS**

Ensure all panels are fully engaged and straight

**11 LAST ROW**

Measure width of panel required - cut with knife

**12 CUTTING AROUND PIPEWORK**

Drill holes 9mm larger than pipe diameter

#### CARE AND MAINTENANCE

- Clean with a damp mop as needed. Do not use abrasive cleaners, bleach or wax to maintain the floor.
- Do not drag or slide heavy objects across the floor.
- 15kg max.
- Clean with a damp mop as needed. Do not use abrasive cleaners, bleach or wax to maintain the floor.
- Residential steam mops are allowed but please use at the lowest setting with a suitable soft pad (refer to the manufacturer's instructions for proper usage).
- Use proper floor protection devices such as felt protectors under furniture. Do not use mats with a latex or rubber backing as these can cause permanent discoloration.
- Place a walk-off mat at outside entrances to reduce the amount of dirt brought into your home to keep your floors cleaner for longer.

<b>CE</b> Howden Joinery Group Plc 40 Portman Square, London W1A 1LT 13 HJ-018-JC EN 14041:2004 Resistant floor covering - EN ISO 10582 Reaction to fire (EN 13501-1): B <sub>1</sub> - S <sub>1</sub> Content of Pentachlorophenol: No Pentachlorophenol containing products added Emission of formaldehyde: E1 Slip resistance: DS Thermal Conductivity: NPD	<b>UK CA</b> Howden Joinery Group Plc 40 Portman Square, London W1A 1LT 21 HJ-018-JC EN 14041: 2004/AC:2006 Reaction to fire (EN 13501-1): B <sub>1</sub> - S <sub>1</sub> Formaldehyde emission (EN717-1): E1 Slip resistance (EN 13893): DS Thermal Conductivity: 0.123 W/mK
--	---

Imported in EU by: Houdan Cuisines SAS, Z.A. du Bois Rigault Nord, 1 Rue Culmette, 62080 Vendin-le-Vieil, Cedex, France.

OAKE & GRAY  
BEAUTIFUL FLOORING IN A SINGLE CLICK

RIGID LUXURY VINYL  
with underlay

SDH3705

Ivory  
Rigid Luxury Vinyl with Underlay  
600 x 300 x 5 mm  
13 pcs = 2.34m<sup>2</sup>  
Weight = 19.77kg



Scan this QR code to find full fitting instructions




600 x 300 x 5 mm  
13 panels per pack  
Coverage 2.34m<sup>2</sup>  
Pack weight: 19.77kg

SDH3705


Ivory  
Rigid Luxury Vinyl with Underlay  
600 x 300 x 5 mm  
13 pcs = 2.34m<sup>2</sup>  
Weight = 19.77kg



TEXTURED SURFACE  
IS DIRT, STUFF AND  
STAIN RESISTANT




INTEGRATED UNDERLAY  
CAN BE USED OVER  
EXISTING HARD FLOORING



100% WATERPROOF




SUITABLE FOR BATHROOMS  
AND CONSERVATORIES



SUITABLE FOR  
UNDERFLOOR HEATING



QUICK CLICK,  
NO GLUE REQUIRED\*



V-GROOVE WITH  
PAINTED BEVEL

\* Please refer to full fitting instructions for details.

OAKE & GRAY

BEAUTIFUL FLOORING IN A SINGLE CLICK

RIGID LUXURY VINYL  
with underlay

OAKE & GRAY

BEAUTIFUL FLOORING IN A SINGLE CLICK

RIGID LUXURY VINYL  
with underlay

SDH3705

Ivory  
Rigid Luxury Vinyl with Underlay  
600 x 300 x 5 mm  
13 pcs = 2.34m<sup>2</sup>  
Weight = 19.77kg



SDH3705

Ivory  
Rigid Luxury Vinyl with Underlay  
600 x 300 x 5 mm  
13 pcs = 2.34m<sup>2</sup>  
Weight = 19.77kg

