

size: 1551x240x39mm

OAKE & GRAY

BEAUTIFUL FLOORING IN A SINGLE CLICK

XL RIGID LUXURY VINYL with underlay

IMPORTANT VINYL FLOORING FITTING NOTICE

- Fitting method for this product is unique and laying instructions must be followed. Store packs in a room with a minimum temperature of 20°C - 25°C.
- Do not open packs until you are ready to install the flooring and mix/shuffle panels from different packs when installing.
- Subfloor must be flat, smooth, clean, and dry. (Do not install in areas with high flooding risk such as saunas or outdoors).
- Use spacers to create the required expansion gap (6mm) around the edge of the room and all fixed objects including door frames, radiator pipes and cabinet legs.
- Do not install kitchen cabinets on top of the flooring.
- All joints should be tapped in to place using a rubber mallet and an off-cut piece of flooring (tapping block). No gaps should be visible.
- Ensure each row is checked for straightness before starting the following row.
- Short joints should be a minimum of 200mm apart from the short end joint on the previous row.
- Use a straight edge to score the plank several times (decor facing upwards) then snap for a clean break.

PRE-INSTALLATION

CLEAN THE SUB-FLOOR

- SMOOTH
- CLEAN
- DRY
- SOUND

CHECK SUB-FLOOR MOISTURE CONTENT

MINERAL BASED	TIMBER BASED
✓ DPM OR ✓ BREATHABLE MOISTURE BARRIER (e.g. Siluxen moisture barrier paper can be used)	✓ 8 - 12% moisture content
✓ CONCRETE ✓ GROUT SCHEDULE ✓ MORTAR SET	✓ BREATHABLE MOISTURE BARRIER (e.g. Siluxen moisture barrier paper can be used)
	✓ FLOORSERVE ✓ COMPOSOL ✓ PIVWOOD

NOTE: Additional expansion gap required for runs longer than 20m (or areas exceeding 400m²) in the form of a threshold strip.

UNDERFLOOR HEATING
Water and electric systems can be used.

Gradually increase the temperature by 5° PER DAY UP TO A MAX OF 30°

SEEK ADVICE FROM UNDERFLOOR HEATING MANUFACTURER

OAKE & GRAY
BEAUTIFUL FLOORING IN A SINGLE CLICK

XL RIGID LUXURY VINYL with underlay

XL RIGID LUXURY VINYL with underlay

SDH3850

EN 14061 : 2004 AAC 2006

Reaction to fire (EN 13501-1) : B_s - S₁

Formaldehyde emission (EN 717-1) : E1

Slip resistance (EN 13893) : DS

Thermal Conductivity : 0.123 W/mK

OAKE & GRAY

BEAUTIFUL FLOORING IN A SINGLE CLICK

XL RIGID LUXURY VINYL with underlay

CARE AND MAINTENANCE

- Clean with a damp mop as needed. Do not use abrasive cleaners, bleach or wax to maintain the floor.
- Do not drag or slide heavy objects across the floor.
- Residential steam mops are allowed but please use at the lowest setting with a suitable soft pad (refer to the manufacturer's instructions for proper usage).
- R9sg max.
- Use proper floor protection devices such as felt protectors under furniture. Do not use mats with a latex or rubber backing as these can cause permanent discoloration.
- Place a walk-off mat at outside entrances to reduce the amount of dirt brought into your home to keep your floors cleaner for longer.

SDH3850

EN 14061 : 2004 AAC 2006

Reaction to fire (EN 13501-1) : B_s - S₁

Formaldehyde emission (EN 717-1) : E1

Slip resistance (EN 13893) : DS

Thermal Conductivity : 0.123 W/mK

OAKE & GRAY
BEAUTIFUL FLOORING IN A SINGLE CLICK

XL RIGID LUXURY VINYL with underlay

XL RIGID LUXURY VINYL with underlay

SDH3850

EN 14061 : 2004 AAC 2006

Reaction to fire (EN 13501-1) : B_s - S₁

Formaldehyde emission (EN 717-1) : E1

Slip resistance (EN 13893) : DS

Thermal Conductivity : 0.123 W/mK

OAKE & GRAY

BEAUTIFUL FLOORING IN A SINGLE CLICK

XL RIGID LUXURY VINYL with underlay

CARE AND MAINTENANCE

- Clean with a damp mop as needed. Do not use abrasive cleaners, bleach or wax to maintain the floor.
- Do not drag or slide heavy objects across the floor.
- Residential steam mops are allowed but please use at the lowest setting with a suitable soft pad (refer to the manufacturer's instructions for proper usage).
- R9sg max.
- Use proper floor protection devices such as felt protectors under furniture. Do not use mats with a latex or rubber backing as these can cause permanent discoloration.
- Place a walk-off mat at outside entrances to reduce the amount of dirt brought into your home to keep your floors cleaner for longer.

SDH3850

EN 14061 : 2004 AAC 2006

Reaction to fire (EN 13501-1) : B_s - S₁

Formaldehyde emission (EN 717-1) : E1

Slip resistance (EN 13893) : DS

Thermal Conductivity : 0.123 W/mK

OAKE & GRAY

BEAUTIFUL FLOORING IN A SINGLE CLICK

XL RIGID LUXURY VINYL with underlay

CARE AND MAINTENANCE

- Clean with a damp mop as needed. Do not use abrasive cleaners, bleach or wax to maintain the floor.
- Do not drag or slide heavy objects across the floor.
- Residential steam mops are allowed but please use at the lowest setting with a suitable soft pad (refer to the manufacturer's instructions for proper usage).
- R9sg max.
- Use proper floor protection devices such as felt protectors under furniture. Do not use mats with a latex or rubber backing as these can cause permanent discoloration.
- Place a walk-off mat at outside entrances to reduce the amount of dirt brought into your home to keep your floors cleaner for longer.

SDH3850

EN 14061 : 2004 AAC 2006

Reaction to fire (EN 13501-1) : B_s - S₁

Formaldehyde emission (EN 717-1) : E1

Slip resistance (EN 13893) : DS

Thermal Conductivity : 0.123 W/mK

OAKE & GRAY

BEAUTIFUL FLOORING IN A SINGLE CLICK

XL RIGID LUXURY VINYL with underlay

CARE AND MAINTENANCE

- Clean with a damp mop as needed. Do not use abrasive cleaners, bleach or wax to maintain the floor.
- Do not drag or slide heavy objects across the floor.
- Residential steam mops are allowed but please use at the lowest setting with a suitable soft pad (refer to the manufacturer's instructions for proper usage).
- R9sg max.
- Use proper floor protection devices such as felt protectors under furniture. Do not use mats with a latex or rubber backing as these can cause permanent discoloration.
- Place a walk-off mat at outside entrances to reduce the amount of dirt brought into your home to keep your floors cleaner for longer.

SDH3850

EN 14061 : 2004 AAC 2006

Reaction to fire (EN 13501-1) : B_s - S₁

Formaldehyde emission (EN 717-1) : E1

Slip resistance (EN 13893) : DS

Thermal Conductivity : 0.123 W/mK

OAKE & GRAY

BEAUTIFUL FLOORING IN A SINGLE CLICK

XL RIGID LUXURY VINYL with underlay

CARE AND MAINTENANCE

- Clean with a damp mop as needed. Do not use abrasive cleaners, bleach or wax to maintain the floor.
- Do not drag or slide heavy objects across the floor.
- Residential steam mops are allowed but please use at the lowest setting with a suitable soft pad (refer to the manufacturer's instructions for proper usage).
- R9sg max.
- Use proper floor protection devices such as felt protectors under furniture. Do not use mats with a latex or rubber backing as these can cause permanent discoloration.
- Place a walk-off mat at outside entrances to reduce the amount of dirt brought into your home to keep your floors cleaner for longer.

SDH3850

EN 14061 : 2004 AAC 2006

Reaction to fire (EN 13501-1) : B_s - S₁

Formaldehyde emission (EN 717-1) : E1

Slip resistance (EN 13893) : DS

Thermal Conductivity : 0.123 W/mK

OAKE & GRAY</