

size: L1254mm x W193mm x H53mm

C:91
M:46
Y:58
K:65

C:5
M:75
Y:82
K:0

OAKE & GRAY
BEAUTIFUL FLOORING IN A SINGLE CLICK

RIGID LUXURY VINYL
with underlay

IMPORTANT VINYL FLOORING FITTING NOTICE

- Fitting is essential for the product to behave and to lay in accordance with the relevant Standard. Check the room with a minimum temperature of 20°C - 25°C.
- Do not open packs until you are ready to install the flooring and unroll panels from different packs when installing.
- Subfloor must be flat, smooth, clean and dry. Do not install in areas with high humidity (such as showers or outdoors).
- Use spacers to create the required expansion gap (8mm).
- Use the edge of the room and all fixed objects including door frames, radiator pipes and cabinet legs.
- Do not install kitchen cabinets on top of the flooring.
- All joints should be tapered in to place using a rubber mallet and an off-cut piece of flooring (keeping black).
- No gaps should be visible.
- Some cuts must be checked for sharpness before starting the following row.
- Sharp joints should have a minimum of 200mm apart from the splice and joint on the previous row.
- Do not install on stone tiles or concrete (check with your distributor, always downwards), then ready for a clean break.

PRE-INSTALLATION

CLEAN THE SUB-FLOOR → SMOOTH → CLEAN → DRY → SOUND

CHECK SUB-FLOOR MOISTURE CONTENT

WATER RESIST

- ✓ Use a moisture meter
- ✓ Use a moisture meter
- ✓ Use a moisture meter
- ✓ Use a moisture meter

NOTE: Additional requirements for rooms longer than 9m for areas exceeding 60m² in the form of a separate drawing.

UNDER-FLOOR HEATING AND ELECTRIC systems can be used.

SEEK ADVICE FROM UNDER-FLOOR HEATING MANUFACTURER.

INSTALLATION (not suitable for external installation)

- 1 CHOOSE DIRECTION OF INSTALLATION**
- 2 FIRST ROW**
- 3 LAY FIRST ROW - engage and joints**
- 4 USE SPACERS AROUND EDGE**
- 5 MEASURE AND CUT**
- 6 CHECK ROW IS STRAIGHT**
- 7 USE OFF-CUT FOR NEXT ROW**
- 8 FULLY ENGAGED PANEL JOINTS**
- 9 FIT NEXT PANEL**
- 10 REPEAT FOR ALL PANELS**
- 11 LAST ROW**
- 12 CUTTING AROUND PIPEWORK**

CARE AND MAINTENANCE

- Use a proper floor protection device such as felt protectors and mats to prevent dirt from being tracked onto the floor.
- Do not drag or slide heavy objects across the floor.
- Residual clean marks may be lifted, but always use all the floor mats and mats.
- Do not use bleach or other acids for floor cleaning.
- Use a proper floor protection device such as felt protectors and mats to prevent dirt from being tracked onto the floor.
- Do not place objects heavier than 15kg on top of the floor.

CE

UKCA

UK

40 Phoenix Bazaar, London W6 8ET
HULLADAC
EN 14041 : 2004/A2:2008
Reaction to fire (EN 13501-1): B_s - B₁
Formaldehyde emission (EN 1717-1): E₁
Slip Resistance (EN 13893): DS
Thermal Conductivity: 0,122 W/mK

Important! If slip-resistance classes are A or B on human feet, 1000 Jaminet, 42061, 02081, 02081, 02081, 02081, 02081.



Scan this QR code to find full fitting instructions



1235mm x 178mm x 5mm
10 panels per pack
Coverage 2.2m²
Pack weight: 18.36kg

SDH3690
TIMELESS OAK
RIGID LUXURY VINYL
with underlay
4 895 216 195 17099

RIGID LUXURY VINYL with underlay

- 100% WATERPROOF
- INTERLOCKED UNDERLAY
- CAN BE USED OVER EXISTING HARD FLOORING*
- TEXTURED SURFACE
- DENT, SCUFF AND STAIN RESISTANT
- QUICK CLICK - NO GLUE REQUIRED*
- SUITABLE FOR BATHROOMS AND CONSERVATORIES
- SUITABLE FOR UNDER-FLOOR HEATING
- V-GROOVE WITH PAINTED BEVEL

*Please refer to full fitting instructions for details.

OAKE & GRAY
BEAUTIFUL FLOORING IN A SINGLE CLICK

RIGID LUXURY VINYL with underlay

SDH3690
TIMELESS OAK
RIGID LUXURY VINYL
1235 x 178 x 5 mm (incl. 1 mm Sound Absorbing Pad)
Wear Layer: 0.55mm
100% PVC
4 895 216 195 17099

SDH3690
TIMELESS OAK
RIGID LUXURY VINYL
with underlay
4 895 216 195 17099

SDH3690
TIMELESS OAK
RIGID LUXURY VINYL
with underlay
4 895 216 195 17099

OAKE & GRAY
BEAUTIFUL FLOORING IN A SINGLE CLICK