

SDH3605 Howdens Professional Fast Fit light oak chevron 2.53m²



Associated products	
Threshold strip (L900mm)	P SDH6420
Ramp strip (L900mm)	P SDH6430
Scotia (L2.4m)	P SDH6450
Light Oak Pipe rose (Pack of 2)	SDH7790

Construction	
Construction	Laminated
Surface layer	Direct laminated papers, papers impregnated with melamine resin
Substrate	Moisture resistant E1 HDF
Backing	0.1mm Counteracting laminate
Aqua Block details	Suitable for kitchens, bathrooms, and other areas prone to high moisture content levels (excluding wet rooms)

Technical Information	
Range	Decorative Tiles
Flooring format	Chevron
Max room dimensions - length	12 m
Max room dimensions - width	8 m
Locking system	Click Fit Glueless
Finish	Registered embossed
Glue / resin	Melamine Resin
Moisture content	EN 13329 - Table 3; 4% - 10%
Impact resistance	EN 13329 - Class IC2
Abrasion class	AC5 - heavy commercial use
Light fastness	EN 20105 / EN ISO 105
Reaction to fire	EN 13501-1 CFL s2

Technical Information	
Level of use of according to EN13329*	Class 33 (Heavy Commercial) Class 23 (Heavy Domestic)
Thermal conductivity	0.14 W/mK
Effect of castor chairs	EN 13329 No change in appearance or damage, as defined in EN425 "Type W"
Resistance to staining	EN 438 Group 1 + 2 Grade 5 & Group 3 Grade 4
Slip resistance	EN 14041 Technical Class NPD (no performance determined)
Formaldehyde emission	Class E1

Dimensions & packaging	
Product dimensions metric	W293.4mm x L1184mm x D8mm
Product weight	18.136kg
Quantity	5
Product packed dimension	H48mm x W1310mm x D340mm
Volume coverage / pack size	2.08 m/sq
Product packed weight	18.31kg

Key

F = FSC® C019676

P = PEFC™

UK = UK Manufactured

† = Subject to availability