

# SDH2402 Quickstep Impressive



Quickstep Impressive Oak	SDH2402
--------------------------	---------

Construction	
Construction	Laminated
Aqua Block details	Suitable for wet areas including kitchens and bathrooms, but NOT wetrooms

Technical Information	
Range	Impressive Flooring
Locking system	Uniclic
Glue / resin	Internal recipe - cannot be supplied to customer
Impact resistance	EN 13329 - Class IC2
Abrasion class	AC4 - medium commercial use
Light fastness	EN 13329 Blue Wool Scale ≤ 6 / Grey Scale ≤ 4
Reaction to fire	EN 14041 Class Cfl - s1
Level of use of according to EN13329*	Class 32 (General Commercial)
Suitable for underfloor heating detail	Yes - If installed as per the instructions (note must not exceed 28 degrees )
Effect of castor chairs	EN 13329 No change in appearance or damage, as defined in EN425 "Type W"
Resistance to staining	EN 13329 - Group 1 + 2 (Grade 5) & Group 3 (Grade 4)
Slip resistance	EN 13893 Technical Class DS
Formaldehyde emission	E1 = 0.1 PPM

Technical Information	
Laying detail	Must be laid as a floating floor (see instructions)

Dimensions & packaging	
Product dimensions metric	W190mm xL1,380mm x D8mm
Product weight	12.57kg
Quantity	7
Product packed dimension	H57mm x W1,405mm x D208mm
Volume coverage / pack size	1.8350 m/sq
Product packed weight	13.17kg

## Key

- F** = FSC®
- P** = PEFC™
- UK** = UK Manufactured
- †** = Subject to availability



## Care & Installation

Care and maintenance	<p>Use the floor exclusively under the recommended conditions in the instructions</p> <p>Regular cleaning with a well wrung out cloth/mop is advised</p> <p>Do not use steam mops or cleaners</p> <p>Do not leave any water on the floor, wipe up any spills immediately</p> <p>Do not use cleaning agents such as wax, polish or oil</p> <p>Direct sunlight may have an effect on the floor over a period of time</p> <p>All spills MUST be wiped up immediately</p> <p>A well rung out mop can also be used periodically, however avoid the use of excess water</p> <p>We recommend that floor mats are used at entrances to the property where timber flooring is installed. This will help avoid abrasive particles damaging the surface.</p> <p>Self-adhesive pads and castor cups should be fitted to furniture to avoid scratching where applicable. Note: Heavy scratching could break the seal on the flooring causing damage</p> <p>General cleaning of the floor should be done using a soft broom or vacuum cleaner. Do not use abrasive cleaners, steel wool or scouring pads, as they will damage the floor.</p> <p>For full details please see the finishing instructions provided with the flooring</p>
Fitting instructions	<p>For full details please see the fitting instructions supplied with the flooring.</p>
Important notes	<p>Remove all previous floor covering</p> <p>Sealed packs should be kept in the room where they are to be laid for 48 hours or more to allow them to acclimatize to the ambient temperature and humidity.</p> <p>Must leave a 12mm expansion gap around the entire floor including cabinet legs, radiator pipes and door frames</p> <p>Do not install cabinets over the floor</p> <p>The maximum area without additional expansion joints is 8m width x 8m length</p> <p>Wet areas include kitchens and bathrooms, but NOT wetrooms</p>
Bathroom installation	<p>For full details please see the fitting instructions supplied with the flooring.</p>

