

SDH2401 Quickstep Impressive



Quickstep Impressive Grey Oak	SDH2401
-------------------------------	---------

Construction	
Construction	Laminated
Aqua Block details	Suitable for wet areas including kitchens and bathrooms, but NOT wetrooms

Technical Information	
Range	Impressive Flooring
Locking system	Uniclic
Glue / resin	Internal recipe - cannot be supplied to customer
Impact resistance	EN 13329 - Class IC2
Abrasion class	AC4 - medium commercial use
Light fastness	EN 13329 Blue Wool Scale ≤ 6 / Grey Scale ≤ 4
Reaction to fire	EN 14041 Class Cfl - s1
Level of use of according to EN13329*	Class 32 (General Commercial)
Suitable for underfloor heating detail	Yes - If installed as per the instructions (note must not exceed 28 degrees)
Effect of castor chairs	EN 13329 No change in appearance or damage, as defined in EN425 "Type W"
Resistance to staining	EN 13329 - Group 1 + 2 (Grade 5) & Group 3 (Grade 4)
Slip resistance	EN 13893 Technical Class DS
Formaldehyde emission	E1 = 0.1 PPM

Technical Information	
Laying detail	Must be laid as a floating floor (see instructions)

Dimensions & packaging	
Product dimensions metric	W190mm xL1,380mm x D8mm
Product weight	12.57kg
Quantity	7
Product packed dimension	H57mm x W1,405mm x D208mm
Volume coverage / pack size	1.8350 m/sq
Product packed weight	13.17kg

- Key**
- F** = FSC®
 - P** = PEFC™
 - UK** = UK Manufactured
 - †** = Subject to availability



Care & Installation

Care and maintenance	<p>Use the floor exclusively under the recommended conditions in the instructions</p> <p>Regular cleaning with a well wrung out cloth/mop is advised</p> <p>Do not use steam mops or cleaners</p> <p>Do not leave any water on the floor, wipe up any spills immediately</p> <p>Do not use cleaning agents such as wax, polish or oil</p> <p>Direct sunlight may have an effect on the floor over a period of time</p> <p>All spills MUST be wiped up immediately</p> <p>A well rung out mop can also be used periodically, however avoid the use of excess water</p> <p>We recommend that floor mats are used at entrances to the property where timber flooring is installed. This will help avoid abrasive particles damaging the surface.</p> <p>Self-adhesive pads and castor cups should be fitted to furniture to avoid scratching where applicable. Note: Heavy scratching could break the seal on the flooring causing damage</p> <p>General cleaning of the floor should be done using a soft broom or vacuum cleaner. Do not use abrasive cleaners, steel wool or scouring pads, as they will damage the floor.</p> <p>For full details please see the finishing instructions provided with the flooring</p>
Fitting instructions	<p>For full details please see the fitting instructions supplied with the flooring.</p>
Important notes	<p>Remove all previous floor covering</p> <p>Sealed packs should be kept in the room where they are to be laid for 48 hours or more to allow them to acclimatize to the ambient temperature and humidity.</p> <p>Must leave a 12mm expansion gap around the entire floor including cabinet legs, radiator pipes and door frames</p> <p>Do not install cabinets over the floor</p> <p>The maximum area without additional expansion joints is 8m width x 8m length</p> <p>Wet areas include kitchens and bathrooms, but NOT wetrooms</p>
Bathroom installation	<p>For full details please see the fitting instructions supplied with the flooring.</p>

