

SDH3684 Quick-Step Livyn cottage dark brown oak



- Key**
- F** = FSC®
 - P** = PEFC™
 - UK** = UK Manufactured
 - †** = Subject to availability

Associated products	
SelitBloc® Vinyl underlay 1.18m x 8.5m x 1.5mm	SDH0926
Dark Oak Scotia (L2.4m)	NEW UK P SDH6850
Clear edge T-Bar	SDH4120
Chrome pipe rose Pack of 4	SDH0895
Vinyl Flooring Roller	SDH9013

Construction	
Surface layer	0.3mm Clear Wear Layer
Substrate	4.5mm PVC

Technical Information	
Range	Vinyl Flooring
Flooring format	Single plank
Locking system	Click Fit Glueless
Finish	Textured
Glue / resin	Internal recipe - cannot be supplied to customer
Moisture content	N/A
Impact resistance	EN 13329 - Class IC2
Abrasion class	AC4 - medium commercial use
Light fastness	EN 13329 Blue Scale class 6
Reaction to fire	Class Efi - EN14041
Level of use of according to EN13329*	Class 23 (Heavy Domestic) Class 32 (General Commercial)
Thermal conductivity	0.015 W/mK
Effect of castor chairs	EN 13329- 25,000 cycles no change

Technical Information	
Resistance to staining	EN 438 Group 1 + 2 Grade 5 & Group 3 Grade 4 EN 13329 - Group 1 + 2 (Grade 5) & Group 3 (Grade 4)
Slip resistance	EN 13893 Technical Class DS
Formaldehyde emission	E1 - < 0.025 PPM - EN 717-1
Laying detail	Must be laid as a floating floor (see instructions)
Suitable for underfloor heating	Yes - Electric and radiant if installed as per the instructions (note must not exceed 27 degrees)
Fitting instructions	Underfloor heating systems (water / electrical) should be built into a layer of screed when used in conjunction with Quick-Step Livyn flooring and kept at a constant room temperature of 18°C (64°F) during installation and for 48h after installation. Once installed the floor surface temperature must not go above a maximum of 27°C (80°C). Separate rooms or rooms with different underfloor heating systems should be installed with a transition profile.

Dimensions & packaging	
Product dimensions metric	L1250mm x W187mm x D4.5mm
Product weight	17.1kg
Quantity	9
Product packed dimension	H42mm x W1,278mm x D202mm
Volume coverage / pack size	2.105 m/sq



Dimensions & packaging

Product packed weight	17.5kg
-----------------------	--------

