

Howdens High Performance XPS Underlay

SDH0909

Pack Contents:	18 Boards
Pack Coverage:	10.8 m
Panel Size:	600mm x 1000mm
Panel Thickness:	5mm
Pack Weight:	1.67Kgs




Impact Noise Reduction
20db




Outstanding Thermal Insulation -
Conductivity 0.024 W/m k




10 t/m²
Compression Strength



Excellent Levelling
Properties



1.67kgs
Light Weight
Easy to Handle



Ideal for all Wood &
Laminate Flooring

Installation

Surface Preparation

- The floor should be clean, dry and free of dust
- Any loose floorboards should be nailed down and any protruding nails hammered flush
- Always use Howdens Joinery Damp Proof Membrane on concrete/screed based sub floors
- Check with Underfloor Heating Manufacturer for underlay suitability

Laying Instructions

- The underlay board can be easily cut using a knife
- The boards must be kept dry
- Lay the boards in a staggered pattern to spread the joints
- Leave a 5mm gap around all edges to allow for any expansion
- You must always lay your final floor coverings as directed by the flooring manufacturer



Howdens High Performance XPS Underlay

Pack Contents:	18 Boards
Pack Coverage:	10.8 m ²
Panel Size:	600mm x 1000mm
Panel Thickness:	5mm
Pack Weight:	1.67kgs



SDH 0909