

Linear Smooth Glazed



Construction	
Construction material	Softwood frame, butt jointed and stapled
Core material thickness	25 mm
Country of origin	UK
Lock block height	360 mm
Lock block width	65 mm
Lock block position	Fitted centrally, to one side only - If the lock block is not indicated by the word 'LOCK' on the top edge, a hole will always be visible on the bottom edge on the side of the lock block.
Glazing style	Clear

Edging Information		
	Lipping dimensions	Maximum trim
Top		6 mm
Bottom		6 mm
Each side		6 mm
Edging additional information	An equal amount of timber should be removed from each side/ top & bottom. Remaining within the parameters of the maximum trim instructions ensures the construction of the door is not compromised.	

Fitting and finishing

Doors must be sealed on all edges prior to installation.
For identification, the Howdens logo, SKU code and batch number is on the top edge of the door.
Howdens doors do have Kite markings, however it is not a legal requirement to be visible on every door.
Please refer to door instruction manual for all fitting information
Ready for priming and painting
Glazing certificate available

Dimensions										
Product code	Product height	Product width	Product thickness	Product weight	Building regulations	Top rail	Glazing height	Glazing width	Glazing thickness	Bottom rail
DGM2140 NEW UK	6'6" / 1981mm	2'3" / 686mm	35mm	15.762kg		110mm	1,473mm	204mm	4mm	185mm
DGM2160 NEW UK	6'6" / 1981mm	2'6" / 762mm	35mm	15.762kg		110mm	1,473mm	204mm	4mm	185mm
DGM2170 NEW UK	6'6" / 1981mm	2'9" / 838mm	35mm	15.762kg	M	110mm	1,473mm	204mm	4mm	185mm

Key information

All sizes subject to standard industry tolerances

M = Part M - Mobility and access*

L = Part L - Warmth & insulation suitable for new build*

L = Part L - Warmth & insulation suitable for refurbishment projects*

E = Part E - Reduction of sound travel*

FD30/60/120 = Certified fire door*

F = Forest Stewardship Council (FSC®)*

P = Programme for the Endorsement of Forest Certification schemes (PEFC™)*

UK = UK Manufactured

† = Subject to availability

*Not applicable to all doors, please see the Dimensions table above for products that meet these standards