## **Metro Smooth Glazed**



Construction material	Softwood timber frame butt jointed and stapled				
Material core	Honeycomb (25mm cell width)				
Core material thickness	25 mm				
Country of origin	UK				
Lock block height	360 mm				
Lock block width	65 mm				
Lock block position	Fitted centrally, to one side only - If the lock block is not indicated by the word 'LOCK' on the top edge, a hole will always be visible on the bottom edge on the side of the lock block.				
Glazing fixing method	Beading and Pinned				
Glazing style	Clear				

Edging Information							
	Lipping dimensions	Maximum trim					
Тор		6 mm					
Bottom		6 mm					
Each side		6 mm					
Edging additional information	be removed from ea & bottom. Remainin parameters of the m instructions ensures	amount of timber should red from each side/ top n. Remaining within the ers of the maximum trim ons ensures the construction or is not compromised.					

## Fitting and finishing

Howdens doors do have Kite markings, however it is not a legal requirement to be visible on every door. Please refer to door instructions for all fitting information. For identification, the Howdens logo, SKU code and batch number is on the top edge of the door.

Ready for priming and painting

Glazing certificate available

Version: 7.B.M

Dimensions										
Product code	Product height	Product width	Product thickness	Product weight	Building regulations	Top rail	Glazing height	Glazing width	Glazing thickness	Bottom rail
DGM2240 <b>UK</b>	6'6" / 1981mm	2'3" / 686mm	35mm	12.04kg		110mm	1,473mm	204mm	4mm	185mm
DGM2260 <b>UK</b>	6'6" / 1981mm	2'6" / 762mm	35mm	13.913kg		110mm	1,473mm	204mm	4mm	185mm
DGM2270 <b>UK</b>	6'6" / 1981mm	2'9" / 838mm	35mm	15.762kg	м	110mm	1,473mm	204mm	4mm	185mm

Key information

All sizes subject to standard industry tolerances

M = Part M - Mobility and access\*

L = Part L - Warmth & insulation suitable for new build\*

L = Part L - Warmth & insulation suitable for refurbishment projects\*

**E** = Part E - Reduction of sound travel\*

FD30/60/120 = Certified fire door\*

**F** = Forest Stewardship Council (FSC<sup>®</sup>)\*

**P** = Programme for the Endorsement of Forest Certification schemes (PEFC<sup>™</sup>)\*

**UK** = UK Manufactured

+ = Subject to availability

\*Not applicable to all doors, please see the Dimensions table above for products that meet these standards

Version: 7.B.M