

Solid Rustic Oak ledged



Construction	
Construction	Ledged
Construction material	Solid timber construction
Material core	White Oak - Comsel
Core material thickness	20 mm
Lock block additional information	A Suffolk latch or a Rim lock is recommended with this door.

Edging Information		
	Lipping dimensions	Maximum trim
Top		230 mm
Bottom		230 mm
Each side		20 mm
Edging additional information	An equal amount of timber should be removed from each side/ top & bottom. Remaining within the parameters of the maximum trim instructions ensures the construction of the door is not compromised.	

Fitting and finishing

Please refer to door instructions for all fitting information. For identification, the Howdens logo, SKU code and batch number is on the top edge of the door. This door is not suitable for waxes, polishes and/or oils (except Osmo Oil) as these products do not seal the door properly and may cause veneer delamination.

Ready for finishing with varnish, stain, paint or Osmo Oil

Dimensions					
Product code	Product height	Product width	Product thickness	Product weight	Building regulations
DIE3430	6'6" / 1981mm	2'0" / 610mm	40mm	19.863kg	
DIE3440	6'6" / 1981mm	2'3" / 686mm	40mm	22.35kg	
DIE3460	6'6" / 1981mm	2'6" / 762mm	40mm	24.831kg	
DIE3470	6'6" / 1981mm	2'9" / 838mm	40mm	28.815kg	M

Key information

All sizes subject to standard industry tolerances

M = Part M - Mobility and access*

L = Part L - Warmth & insulation suitable for new build*

L = Part L - Warmth & insulation suitable for refurbishment projects*

E = Part E - Reduction of sound travel*

FD30/60/120 = Certified fire door*

F = Forest Stewardship Council (FSC®)*

P = Programme for the Endorsement of Forest Certification schemes (PEFC™)*

UK = UK Manufactured

† = Subject to availability

*Not applicable to all doors, please see the Dimensions table above for products that meet these standards