

# Oak foil



Construction	
Construction	Flush
Door construction information	Constructed using softwood timber stile and rail frame
Material core	Honeycomb paper
Country of origin	Various
Lock block height	360 mm
Lock block width	65 mm
Lock block position	Fitted centrally, to one side only - If the lock block is not indicated by the word 'LOCK' on the top edge, a hole will always be visible on the bottom edge on the side of the lock block.

Edging Information		
	Lipping dimensions	Maximum trim
Top		6 mm
Bottom		6 mm
Each side	6 mm	10 mm
Edging additional information	An equal amount of timber should be removed from each side/ top & bottom. Remaining within the parameters of the maximum trim instructions ensures the construction of the door is not compromised.	

## Fitting and finishing

Please refer to door instructions for all fitting information. For identification, the Howdens logo, SKU code and batch number is on the top edge of the door. Doors must be sealed on all edges prior to installation. This door cannot be rebated. Any rebating will expose the pine frame.

Dimensions						
Product code	Product height	Product width	Product thickness	Product weight	Building regulations	Stile
DIL1930 <b>NEW UK</b>	6'6" / 1981mm	2'0" / 610mm	35mm	8.518kg		23mm
DIL1940 <b>NEW UK</b>	6'6" / 1981mm	2'3" / 686mm	35mm	11.25kg		23mm
DIL1960 <b>NEW UK</b>	6'6" / 1981mm	2'6" / 762mm	35mm	12.49kg		23mm
DIL1970 <b>NEW UK</b>	6'6" / 1981mm	2'9" / 838mm	35mm	13.74kg	<b>M</b>	23mm
DIL2040 <b>NEW UK</b>	2040mm	726mm	40mm	12.165kg		23mm
DIL2060 <b>NEW UK</b>	2040mm	826mm	40mm	13.765kg	<b>M</b>	23mm
DIL2070 <b>NEW UK</b>	2040mm	926mm	40mm	15.465kg	<b>M</b>	23mm

#### Key information

All sizes subject to standard industry tolerances

**M** = Part M - Mobility and access\*

**L** = Part L - Warmth & insulation suitable for new build\*

**L** = Part L - Warmth & insulation suitable for refurbishment projects\*

**E** = Part E - Reduction of sound travel\*

**FD30/60/120** = Certified fire door\*

**F** = Forest Stewardship Council (FSC®)\*

**P** = Programme for the Endorsement of Forest Certification schemes (PEFC™)\*

**UK** = UK Manufactured

**†** = Subject to availability

\*Not applicable to all doors, please see the Dimensions table above for products that meet these standards