

Richmond Glazed



| Construction | |
|-----------------------------------|---|
| Construction | Stile and Rail |
| Door construction information | Dowel and glue construction |
| Core material thickness | 44 mm |
| Country of origin | Malaysia |
| Lock block additional information | A lock block is not included on this door as it is a solid construction. The lock can be fitted in any location on either side. |
| Glazing fixing method | Security Glazing Tape, Sealant, Beading, Pins |
| Glazing style | Frosted |

| Edging Information | | |
|--------------------|--------------------|--------------|
| | Lipping dimensions | Maximum trim |
| Top | 19 mm | 5 mm |
| Bottom | 19 mm | 5 mm |
| Each side | 19 mm | 5 mm |

Fitting and finishing

Any trimmed edges and all cut outs for hardware must be refinished
Doors must be sealed on all edges prior to installation.
Howdens doors do have Kite markings, however it is not a legal requirement to be visible on every door.
For identification, the Howdens logo, SKU code and batch number is on the top edge of the door.
Please refer to door instruction manual for all fitting information
Supplied with toughened frosted glass

The company has a policy of continuous product development and reserves the right to change any products and specifications at any time.

| Dimensions | | | | | | | | | | | | |
|------------------|----------------|---------------|-------------------|----------------|----------------------|-------|----------|----------------|---------------|-------------------|-------------|-------------|
| Product code | Product height | Product width | Product thickness | Product weight | Building regulations | Stile | Top rail | Glazing height | Glazing width | Glazing thickness | Bottom rail | Middle rail |
| DXH5460 P | 6'6" / 1981mm | 2'6" / 762mm | 44mm | 39.832kg | | 114mm | 114mm | 898mm | 210mm | 14mm | 180mm | 180mm |
| DXH5470 P | 6'6" / 1981mm | 2'9" / 838mm | 44mm | 42.832kg | M | 114mm | 114mm | 898mm | 248mm | 14mm | 180mm | 180mm |
| DXH5480 P | 6'8" / 2032mm | 2'8" / 813mm | 44mm | 42.832kg | M | 114mm | 114mm | 949mm | 235.5mm | 14mm | 180mm | 180mm |

Key information

All sizes subject to standard industry tolerances

M = Part M - Mobility and access*

L = Part L - Warmth & insulation suitable for new build*

L = Part L - Warmth & insulation suitable for refurbishment projects*

E = Part E - Reduction of sound travel*

FD30/60/120 = Certified fire door*

F = Forest Stewardship Council (FSC®)*

P = Programme for the Endorsement of Forest Certification schemes (PEFC™)*

UK = UK Manufactured

† = Subject to availability

*Not applicable to all doors, please see the Dimensions table above for products that meet these standards