

Pre-finished Dordogne Oak- Fire



Construction	
Construction	Slab
Door construction information	Solid Core Slab Construction
Lock block additional information	A lock block is not included on this door as it is a solid construction. The lock can be fitted in any location on either side.

Fire certification available

Edging Information	
	Maximum trim
Top	0 mm
Bottom	5 mm
Each side	5 mm

The company has a policy of continuous product development and reserves the right to change any products and specifications at any time.

Dimensions						
Product code	Product height	Product width	Product thickness	Product weight	Building regulations	Top rail
DFH7040	6'6" / 1981mm	2'3" / 686mm	44mm	42kg		117mm
DFH7060	6'6" / 1981mm	2'6" / 762mm	44mm	46kg		117mm
DFH7070	6'6" / 1981mm	2'9" / 838mm	44mm	51kg	M	117mm

Key information

All sizes subject to standard industry tolerances

M = Part M - Mobility and access*

L = Part L - Warmth & insulation suitable for new build*

L = Part L - Warmth & insulation suitable for refurbishment projects*

E = Part E - Reduction of sound travel*

FD30/60/120 = Certified fire door*

F = Forest Stewardship Council (FSC®)*

P = Programme for the Endorsement of Forest Certification schemes (PEFC™)*

UK = UK Manufactured

† = Subject to availability

*Not applicable to all doors, please see the Dimensions table above for products that meet these standards