

Linear Oak



Construction	
Construction	Stile and Rail
Door construction information	Veneered particleboard construction
Material core	Particleboard
Core material thickness	35 mm
Veneer thickness	0.6 mm
Country of origin	USA
Lock block additional information	A lock block is not included on this door as it is a solid construction. The lock can be fitted in any location on either side, avoiding mid rail joints as this can weaken the structure of the door.

Edging Information		
	Lipping dimensions	Maximum trim
Top	10 mm	5 mm
Bottom	10 mm	5 mm
Each side	10 mm	5 mm
Edging additional information	An equal amount of timber should be removed from each side/ top & bottom. Remaining within the parameters of the maximum trim instructions ensures the construction of the door is not compromised.	

Fitting and finishing

Please refer to door instructions for all fitting information. For identification, the Howdens logo, SKU code and batch number is on the top edge of the door. This door has a particleboard core which may be exposed if rebated. The use of the oak door pair maker is therefore recommended. This door is not suitable for waxes, polishes and/or oils (except Osmo Oil) as these products do not seal the door properly and may cause veneer delamination.

Dimensions								
Product code	Product height	Product width	Product thickness	Product weight	Building regulations	Stile	Top rail	Bottom rail
DIE2210	6'6" / 1981mm	1'6" / 457mm	35mm	21kg		110mm	110mm	180mm
DIE2220	6'6" / 1981mm	1'9" / 533mm	35mm	24kg		110mm	110mm	180mm
DIE2230	6'6" / 1981mm	2'0" / 610mm	35mm	26.822kg		110mm	110mm	180mm
DIE2240	6'6" / 1981mm	2'3" / 686mm	35mm	29.822kg		110mm	110mm	180mm
DIE2250	6'6" / 1981mm	2'4" / 711mm	35mm	33kg		110mm	110mm	180mm
DIE2260	6'6" / 1981mm	2'6" / 762mm	35mm	33.822kg		110mm	110mm	180mm
DIE2270	6'6" / 1981mm	2'9" / 838mm	35mm	36.822kg	M	110mm	110mm	180mm
DIE2280	6'8" / 2032mm	2'8" / 813mm	35mm	38kg	M	110mm	110mm	180mm
DIE9130	2040mm	626mm	40mm	29.243kg		110mm	110mm	180mm
DIE9140	2040mm	726mm	40mm	33.863kg		110mm	110mm	180mm
DIE9160	2040mm	826mm	40mm	38.863kg	M	110mm	110mm	180mm
DIE9170	2040mm	926mm	40mm	43.243kg	M	110mm	110mm	180mm

Key information

All sizes subject to standard industry tolerances

M = Part M - Mobility and access*

L = Part L - Warmth & insulation suitable for new build*

L = Part L - Warmth & insulation suitable for refurbishment projects*

E = Part E - Reduction of sound travel*

FD30/60/120 = Certified fire door*

F = Forest Stewardship Council (FSC®)*

P = Programme for the Endorsement of Forest Certification schemes (PEFC™)*

UK = UK Manufactured

† = Subject to availability

*Not applicable to all doors, please see the Dimensions table above for products that meet these standards