

# Light Grey 20G glazed



Construction	
Construction	Flush
Door construction information	Constructed using softwood timber stile and rail frame
Material core	Tubeboard or Flaxboard
Core material thickness	37 mm
Country of origin	Various
Lock block additional information	A lock block is not included on this door as it is a solid construction. The lock can be fitted in any location on either side.
Glazing fixing method	Beading and Pinned with intumescent fitted
Glazing stamp details	Visible on glazing unit to comply with legislation
Glazing style	Clear

Edging Information		
	Lipping dimensions	Maximum trim
Top		0 mm
Bottom		6 mm
Each side	6 mm	4 mm

Edging Information	
Edging additional information	An equal amount of timber should be removed from each side. Remaining within the parameters of the maximum trim instructions ensures the construction of the door is not compromised and that the door when fitted complies with the fire certificate.

### Fitting and finishing

Please refer to door instructions for all fitting information. For identification, the Howdens logo, SKU code and batch number is on the top edge of the door. All fire doors must be fitted in accordance with the fire certificate.

Supplied with toughened clear glass

Glazing certificate available

Fire certification available

The company has a policy of continuous product development and reserves the right to change any products and specifications at any time.

Dimensions										
Product code	Product height	Product width	Product thickness	Product weight	Building regulations	Stile	Top rail	Glazing height	Glazing width	Glazing thickness
DFL8060 <b>NEW UK</b>	2040mm	826mm	44mm	28.512kg		27mm	27mm	1,404mm	144mm	6mm
DFL8070 <b>NEW UK</b>	2040mm	926mm	44mm	32.012kg		27mm	27mm	1,404mm	144mm	6mm
DIF8040 <b>UK</b>	6'6" / 1981mm	2'3" / 686mm	44mm	22.689kg	<b>E</b>	27mm	27mm	1,404mm	144mm	6mm
DIF8060 <b>UK</b>	6'6" / 1981mm	2'6" / 762mm	44mm	34.518kg	<b>E</b>	27mm	27mm	1,404mm	144mm	6mm
DIF8070 <b>UK</b>	6'6" / 1981mm	2'9" / 838mm	44mm	37.978kg	<b>E M</b>	27mm	27mm	1,404mm	144mm	6mm

### Key information

All sizes subject to standard industry tolerances

**M** = Part M - Mobility and access\*

**L** = Part L - Warmth & insulation suitable for new build\*

**L** = Part L - Warmth & insulation suitable for refurbishment projects\*

**E** = Part E - Reduction of sound travel\*

**FD30/60/120** = Certified fire door\*

**F** = Forest Stewardship Council (FSC®)\*

**P** = Programme for the Endorsement of Forest Certification schemes (PEFC™)\*

**UK** = UK Manufactured

**†** = Subject to availability

\*Not applicable to all doors, please see the Dimensions table above for products that meet these standards