

Dordogne Oak Glazed



Construction	
Construction	Slab
Door construction information	Slab construction
Core material thickness	44 mm
Country of origin	Malaysia
Lock block additional information	A lock block is not included on this door as it is a solid construction. The lock can be fitted in any location on either side.
Glazing fixing method	Security Glazing Tape, Sealant, Bollection Moulding, Pins
Glazing style	Frosted

Edging Information		
	Lipping dimensions	Maximum trim
Top	20 mm	5 mm
Bottom	20 mm	5 mm
Each side	20 mm	5 mm

Fitting and finishing

Any trimmed edges and all cut outs for hardware must be refinished

Doors must be sealed on all edges prior to installation.

Howdens doors do have Kite markings, however it is not a legal requirement to be visible on every door.

For identification, the Howdens logo, SKU code and batch number is on the top edge of the door.

Please refer to door instruction manual for all fitting information

Supplied triple glazed

Dimensions											
Product code	Product height	Product width	Product thickness	Product weight	Building regulations	Stile	Top rail	Glazing height	Glazing width	Glazing thickness	Bottom rail
DXH2970 F	6'6" / 1981mm	2'9" / 838mm	44mm	41.432kg	M	114mm	114mm	170mm	170mm	14mm	180mm
DXH2980 F	6'8" / 2032mm	2'8" / 813mm	44mm	41.432kg	M	114mm	114mm	170mm	170mm	14mm	180mm

Key information

All sizes subject to standard industry tolerances

M = Part M - Mobility and access*

L = Part L - Warmth & insulation suitable for new build*

L = Part L - Warmth & insulation suitable for refurbishment projects*

E = Part E - Reduction of sound travel*

FD30/60/120 = Certified fire door*

F = Forest Stewardship Council (FSC®)*

P = Programme for the Endorsement of Forest Certification schemes (PEFC™)*

UK = UK Manufactured

† = Subject to availability

*Not applicable to all doors, please see the Dimensions table above for products that meet these standards