

Regent



Construction	
Construction	Stile and Rail
Door construction information	Dowel and glue construction
Core material thickness	44 mm
Country of origin	Malaysia
Lock block additional information	A lock block is not included on this door as it is a solid construction. The lock can be fitted in any location on either side.

Edging Information		
	Lipping dimensions	Maximum trim
Top	19 mm	5 mm
Bottom	19 mm	5 mm
Each side	19 mm	5 mm

Fitting and finishing

Any trimmed edges and all cut outs for hardware must be refinished
Doors must be sealed on all edges prior to installation.
For identification, the Howdens logo, SKU code and batch number is on the top edge of the door.
Please refer to door instruction manual for all fitting information

Dimensions									
Product code	Product height	Product width	Product thickness	Product weight	Building regulations	Stile	Top rail	Bottom rail	Middle rail
DXH4360 P	6'6" / 1981mm	2'6" / 762mm	44mm	38.832kg		114mm	114mm	180mm	180mm
DXH4370 P	6'6" / 1981mm	2'9" / 838mm	44mm	41.832kg	M	114mm	114mm	180mm	180mm
DXH4381 P	6'8" / 2032mm	2'8" / 813mm	44mm	41.832kg	M	114mm	114mm	180mm	180mm

Key information

All sizes subject to standard industry tolerances

M = Part M - Mobility and access*

L = Part L - Warmth & insulation suitable for new build*

L = Part L - Warmth & insulation suitable for refurbishment projects*

E = Part E - Reduction of sound travel*

FD30/60/120 = Certified fire door*

F = Forest Stewardship Council (FSC®)*

P = Programme for the Endorsement of Forest Certification schemes (PEFC™)*

UK = UK Manufactured

† = Subject to availability

*Not applicable to all doors, please see the Dimensions table above for products that meet these standards