

# Thruyton 4 Panel Grained Glazed



Construction	
Construction	Moulded
Door construction information	Constructed using softwood timber stile and rail frame
Material core	Honeycomb paper
Core material thickness	38 mm
Veneer thickness	3 mm
Country of origin	Sweden
Lock block height	360 mm
Lock block width	65 mm
Lock block position	Fitted to one side centrally
Glazing additional information	Suitable for paint finish
Glazing fixing method	Adhesive Tape and Pinned
Glazing stamp details	Visible on each pane to comply with legislation
Glazing style	Clear

Edging Information		
	Lipping dimensions	Maximum trim
Top	10 mm	6 mm
Bottom	10 mm	6 mm
Each side	10 mm	6 mm

Edging Information	
Edging additional information	An equal amount of timber should be removed from each side & bottom. Remaining within the parameters of the maximum trim instructions ensures the construction of the door is not compromised.

### Fitting and finishing

Fit in accordance with data sheet  
Supplied with toughened clear glass  
Glazing certificate available

The company has a policy of continuous product development and reserves the right to change any products and specifications at any time.

Dimensions													
Product code	Product height	Product width	Product thickness	Product weight	Building	Stile	Top rail	Glazing height	Glazing width	Top glazing height	Glazing thickness	Bottom rail	Middle rail
DGM3440 NEW <b>F UK</b>	6'6" / 1981mm	2'3" / 686mm	35mm	10.034kg		23mm	23mm	931mm	205mm	931mm	4mm	23mm	168mm
DGM3460 NEW <b>F UK</b>	6'6" / 1981mm	2'6" / 762mm	35mm	13.034kg		23mm	23mm	931mm	231mm	931mm	4mm	23mm	168mm
DGM3470 NEW <b>F UK</b>	6'6" / 1981mm	2'9" / 838mm	35mm	15.034kg	<b>M</b>	23mm	23mm	931mm	256mm	931mm	4mm	23mm	168mm
DGM3540 NEW <b>F UK</b>	2040mm	726mm	40mm	10.777kg		25mm	25mm	931mm	205mm	931mm	4mm	23mm	168mm
DGM3560 NEW <b>F UK</b>	2040mm	826mm	40mm	12.077kg	<b>M</b>	25mm	25mm	931mm	256mm	931mm	4mm	23mm	168mm

#### Key information

All sizes subject to standard industry tolerances

**M** = Part M - Mobility and access\*

**L** = Part L - Warmth & insulation suitable for new build\*

**L** = Part L - Warmth & insulation suitable for refurbishment projects\*

**E** = Part E - Reduction of sound travel\*

**FD30/60/120** = Certified fire door\*

**F** = Forest Stewardship Council (FSC®)\*

**P** = Programme for the Endorsement of Forest Certification schemes (PEFC™)\*

**UK** = UK Manufactured

**†** = Subject to availability

\*Not applicable to all doors, please see the Dimensions table above for products that meet these standards