

# Internal Hardwood Doors

## Installation, Finishing and Care Instructions

### (Trimable by 10mm on all sides)

\_ j b m q @ ` q ` R b m \_ @ q U b `

It is important you read this leaflet before installing the door. The guidelines below will help ensure the door is fitted correctly and in a suitable environment. Failure to adhere to the instructions could invalidate any warranty claims.

, b b m n \_ r n q H M n q b m M K b ` ^ ] M w M ] H M @ m M m n  
 , b b m n \_ r n q H M \ M j q K m z @ q @ ] ] q U \_ M n  
 , w b U K K U m M I q I b ` q @ I q x U q T n r ` ] U S T q H M R b m M q T M K b b m T @ n H M M ` q m M @ q M K  
 , b ` b q U ` n q @ ] ] b m n q b m M q T M K b b m U ` ` M x ] z j ] @ n q M m M K m b b \_ n  
 , + b ] z q T M ` M x m @ j j U ` S n T b r ] K m M \_ @ U ` b ` q T M K b b m n r ` q U ] U \_ M K U @ q M ] z H M R b m M U ` r  
 , T M I \ q T M K b b m R b m K M R M I q n @ ` K K @ \_ @ S M H M R b m M U ` n q @ ] ] @ q U b ` i b ` b q I b ` q U ` r  
 , ` z n \_ @ ] ] ` U I \ n b m n I m @ q I T M n n T b r ] K H M n @ ` K M K r n U ` S R U ` M n @ ` K j @ j M m H M R b m M c  
 , ` z K b b m x T U I T T @ n H M M ` x b m \ M K b ` I @ ` ` b q H M M y I T @ ` S M K ` x U q T q T M M y I M j q U b ` b F  
 , b b m n n T b r ] K H M T @ ` K ] M K I @ m M R r ] ] z x U q T I ] M @ ` S ] b w M n @ ` K ` b q K m @ S S M K @ I m b n r  
 , b b m n \_ r n q H M n M @ ] M K b ` H b q T R @ I M n @ ` K M K S M n j m U b m q b U ` n q @ ] ] @ q U b `  
 , 2 T U n K b b m I @ ` ` b q H M ] M R q r ` q m M @ q M K @ ` K 3 / 2 ` b q H M ] M R q M y j b n M K q b q T M M ] M \_

## U ` U n T U ` S

As soon as the door is taken out of it's wrapping it should be fully sealed either with the base/primer for the selected finish or with the one part finish chosen. Both faces, all four edges and any cut-outs for hardware must be given the required number of coats as indicated on the manufacturer's instructions, paying particular attention to the end grain. Do not use wire wool or other sanding materials containing steel/iron on our doors. Failing to seal the doors accordingly to our instructions will invalidate any claims.

You can use water based or solvent primers, stains, paints or varnishes to finish this door. If using a solvent based finish we recommend the use of a VOC 2010 compliant product.

# r m K b b m n @ m M ! # 2 n r U q @ H ] M R b m x @ y M n ` j b ] U n T M n ` K z M n b m b U ] n A M @ S @ @ ` U n T #  
 K M I ] @ \_ U ` @ q U b ` b R q T M w M ` M M m @ b x M w M m ` # n \_ b b b m # U ] U n n r U q @ H ] M @

For best results, apply any finishing coat while the door is lying flat. A light sanding between coats will produce the best finish. Adequate drying time must be allowed between coats as indicated in the manufacturers instructions. Failure to follow the above will invalidate claims for excessive movement or de-laminating.

] ] b x K M ` n U ` q M @ ` @ r R U r W q T M H ] M x U q T q T U n K b b m @

## @ ` S U ` S

! b q M o r s for internal use should be fully finished before being hung.

If the door is to be reduced in size, an equal amount of timber should be cut down from either side/top or bottom A j ] M @ n M ` b q M q T @ q  
 \_ r n q ` M w M m j M y ] M M K q U q @ ] M @ I T n U K M A @ All lock or handle cavities should be kept to a minimum size and sited away from  
 rail joint, these areas should then be re-sealed.

Whilst checking the size in the door frame, mark hinge positions and any levers or locks you wish to attach to the door.

## @ U ` q M ` @ ` I M

Regular maintenance of this door should be made in accordance with the stain/paint manufacturers instructions, to prevent breakdown of the wood finish and to protect the timber from deterioration.

In the event of this door being proven to have a manufacturing defect where a replacement is needed, the liability of the seller shall under no circumstance exceed the price of the defective door.

## b ` K U q U b ` n b R / @ ] M

Howdens Joinery will not be held responsible for any incidental work or problems as a result of bad storage, handling or incorrect fitting and finishing of our doors. The foregoing does not affect your statutory rights.