

# Pre-finished Dordogne Smooth Glazed



Construction	
Construction	Moulded
Door construction information	Softwood frame, butt jointed and stapled
Core material thickness	28 mm
Country of origin	UK
Lock block height	320 mm
Lock block width	55 mm
Lock block position	Fitted centrally both sides. Lock block measurements include outer and inner frame.
Glazing fixing method	Beading and Pinned
Glazing stamp details	Howdens glazed doors do have Kite marks, however they are not legally required to be on every door.
Glazing style	Clear

Edging Information		
	Lipping dimensions	Maximum trim
Top	10 mm	6 mm
Bottom	10 mm	6 mm
Each side	10 mm	6 mm
Edging additional information	An equal amount of timber should be removed from each side/ top & bottom. Remaining within the parameters of the maximum trim instructions ensures the construction of the door is not compromised.	

## Fitting and finishing

Please refer to door instructions for all fitting information. This door can be rebated.

For identification, the Howdens logo, SKU code and batch number is on the top edge of the door.

Supplied pre-painted with a white internal face and black or white external face.

Supplied with clear toughened etched glass

Glazing certificate available

Dimensions									
Product code	Product height	Product width	Product thickness	Product weight	Building regulations	Top rail	Glazing width	Glazing thickness	Bottom rail
DGM7530 Regional <b>UK</b>	2040mm	626mm	40mm	14.421kg		101mm		4mm	171mm
DGM7540 Regional <b>UK</b>	2040mm	726mm	40mm	17.491kg		101mm		4mm	171mm
DGM7560 Regional <b>UK</b>	2040mm	826mm	40mm	19.251kg	<b>M</b>	101mm		4mm	171mm
DGM7570 Regional <b>UK</b>	2040mm	926mm	40mm	21.713kg	<b>M</b>	101mm		4mm	171mm
DGM7640 Regional <b>UK</b>	6'6" / 1981mm	2'3" / 686mm	35mm	15.751kg		101mm	467mm	4mm	171mm
DGM7660 Regional <b>UK</b>	6'6" / 1981mm	2'6" / 762mm	35mm	17.491kg		101mm	543mm	4mm	171mm
DGM7670 Regional <b>UK</b>	6'6" / 1981mm	2'9" / 838mm	35mm	19.251kg	<b>M</b>	101mm	619mm	4mm	171mm

#### Key information

All sizes subject to standard industry tolerances

**M** = Part M - Mobility and access\*

**L** = Part L - Warmth & insulation suitable for new build\*

**L** = Part L - Warmth & insulation suitable for refurbishment projects\*

**E** = Part E - Reduction of sound travel\*

**FD30/60/120** = Certified fire door\*

**F** = Forest Stewardship Council (FSC®)\*

**P** = Programme for the Endorsement of Forest Certification schemes (PEFC™)\*

**UK** = UK Manufactured

**†** = Subject to availability

\*Not applicable to all doors, please see the Dimensions table above for products that meet these standards