

Pre-finished Linear Smooth Glazed



Construction	
Construction	Moulded
Country of origin	UK
Lock block height	360 mm
Lock block width	65 mm
Lock block position	Fitted centrally, to one side only - If the lock block is not indicated by the word 'LOCK' on the top edge, a hole will always be visible on the bottom edge on the side of the lock block.
Glazing style	Clear

Edging Information		
	Lipping dimensions	Maximum trim
Top	10 mm	6 mm
Bottom	10 mm	6 mm
Each side	10 mm	6 mm

Fitting and finishing

Any trimmed edges and all cut outs for hardware must be refinished

Can save the builder up to 6 hours on finishing

Doors must be sealed on all edges prior to installation.

For identification, the Howdens logo, SKU code and batch number is on the top edge of the door.

Howdens doors do have Kite markings, however it is not a legal requirement to be visible on every door.

Please refer to door instruction manual for all fitting information

This door is supplied pre-finished

Supplied with toughened clear glass

Dimensions											
Product code	Product height	Product width	Product thickness	Product weight	Building regulations	Stile	Top rail	Glazing height	Glazing width	Glazing thickness	Bottom rail
DGM7240 Regional UK	6'6" / 1981mm	2'3" / 686mm	35mm	16.731kg		110mm	110mm	1,547mm	247mm	4mm	180mm
DGM7260 Regional UK	6'6" / 1981mm	2'6" / 762mm	35mm	18.671kg		110mm	110mm	1,547mm	247mm	4mm	180mm
DGM7270 Regional UK	6'6" / 1981mm	2'9" / 838mm	35mm	20.611kg	M	110mm	110mm	1,547mm	247mm	4mm	180mm

Key information

All sizes subject to standard industry tolerances

M = Part M - Mobility and access*

L = Part L - Warmth & insulation suitable for new build*

L = Part L - Warmth & insulation suitable for refurbishment projects*

E = Part E - Reduction of sound travel*

FD30/60/120 = Certified fire door*

F = Forest Stewardship Council (FSC®)*

P = Programme for the Endorsement of Forest Certification schemes (PEFC™)*

UK = UK Manufactured

† = Subject to availability

*Not applicable to all doors, please see the Dimensions table above for products that meet these standards