

Pre-finished Middleweight Colonial 6 Panel Grained



Construction	
Construction	Stile and Rail
Lock block height	1,981 mm
Lock block width	83 mm
Lock block position	Lock or Latch can be fitted up to 83mm inwards from either edge of the door. The thicker inner stile spans the full length of the door which gives flexibility on where the handle can be fitted. See middleweight doors guide for more details

Edging Information		
	Lipping dimensions	Maximum trim
Top	10 mm	6 mm
Bottom	10 mm	6 mm
Each side	10 mm	6 mm

Fitting and finishing

Any trimmed edges and all cut outs for hardware must be refinished
Can save the builder up to 6 hours on finishing
For identification, the Howdens logo, SKU code and batch number is on the top edge of the door.

Dimensions								
Product code	Product height	Product width	Product thickness	Product weight	Building regulations	Stile	Top rail	Bottom rail
DIM7730 Regional UK	6'6" / 1981mm	2'0" / 610mm	35mm	11.321kg		120mm	117mm	180mm
DIM7740 Regional UK	6'6" / 1981mm	2'3" / 686mm	35mm	12.236kg		120mm	117mm	180mm
DIM7760 Regional UK	6'6" / 1981mm	2'6" / 762mm	35mm	13.121kg		120mm	117mm	180mm
DIM7770 Regional UK	6'6" / 1981mm	2'9" / 838mm	35mm	13.971kg	M	120mm	117mm	180mm

Key information

All sizes subject to standard industry tolerances

M = Part M - Mobility and access*

L = Part L - Warmth & insulation suitable for new build*

L = Part L - Warmth & insulation suitable for refurbishment projects*

E = Part E - Reduction of sound travel*

FD30/60/120 = Certified fire door*

F = Forest Stewardship Council (FSC®)*

P = Programme for the Endorsement of Forest Certification schemes (PEFC™)*

UK = UK Manufactured

† = Subject to availability

*Not applicable to all doors, please see the Dimensions table above for products that meet these standards