

Pre-finished Dordogne Smooth



Construction	
Construction	Moulded
Door construction information	Constructed using softwood timber stile and rail frame
Material core	Honeycomb (25mm cell width)
Core material thickness	28 mm
Lock block height	360 mm
Lock block width	65 mm
Lock block position	Fitted centrally, to one side only - If the lock block is not indicated by the word 'LOCK' on the top edge, a hole will always be visible on the bottom edge on the side of the lock block.

Edging Information		
	Lipping dimensions	Maximum trim
Top	10 mm	6 mm
Bottom	10 mm	6 mm
Each side	10 mm	6 mm
Edging additional information	An equal amount of timber should be removed from each side/ top & bottom. Remaining within the parameters of the maximum trim instructions ensures the construction of the door is not compromised.	

Fitting and finishing

Please refer to door instructions for all fitting information. For identification, the Howdens logo, SKU code and batch number is on the top edge of the door. This door can be rebated. The edges, any trimmed edges and cut outs for hardware must be painted.

Dimensions								
Product code	Product height	Product width	Product thickness	Product weight	Building regulations	Stile	Top rail	Bottom rail
DIM7410 Regional UK	6'6" / 1981mm	1'6" / 457mm	35mm	6.832kg		120mm	117mm	185mm
DIM7420 Regional UK	6'6" / 1981mm	1'9" / 533mm	35mm	7.983kg		82mm	117mm	185mm
DIM7430 Regional UK	6'6" / 1981mm	2'0" / 610mm	35mm	9.153kg		120mm	117mm	185mm
DIM7440 Regional UK	6'6" / 1981mm	2'3" / 686mm	35mm	10.313kg		120mm	117mm	185mm
DIM7450 Regional UK	6'6" / 1981mm	2'4" / 711mm	35mm	11.518kg		133mm	117mm	185mm
DIM7460 Regional UK	6'6" / 1981mm	2'6" / 762mm	35mm	11.463kg		120mm	117mm	185mm
DIM7470 Regional UK	6'6" / 1981mm	2'9" / 838mm	35mm	12.633kg	M	120mm	117mm	185mm
DIM7480 Regional UK	6'8" / 2032mm	2'8" / 813mm	35mm	12.223kg	M	108mm	132mm	221mm
DIM7530 Regional UK	2040mm	626mm	40mm	9.693kg		128mm	132mm	229mm
DIM7540 Regional UK	2040mm	726mm	40mm	12.313kg		140mm	132mm	229mm
DIM7560 Regional UK	2040mm	826mm	40mm	12.823kg	M	114mm	132mm	229mm
DIM7570 Regional UK	2040mm	926mm	40mm	14.413kg	M	125mm	132mm	229mm

Key information

All sizes subject to standard industry tolerances

M = Part M - Mobility and access*

L = Part L - Warmth & insulation suitable for new build*

L = Part L - Warmth & insulation suitable for refurbishment projects*

E = Part E - Reduction of sound travel*

FD30/60/120 = Certified fire door*

F = Forest Stewardship Council (FSC®)*

P = Programme for the Endorsement of Forest Certification schemes (PEFC™)*

UK = UK Manufactured

† = Subject to availability

*Not applicable to all doors, please see the Dimensions table above for products that meet these standards