

Pre-finished Linear Smooth FD30



Construction	
Construction	Moulded
Material core	Flaxboard
Country of origin	UK
Lock block additional information	Only on fire doors: A lock block is not included on fire doors as they are solid construction. The lock can be fitted on them on either side, but the midrail joint must be avoided.

Edging Information		
	Lipping dimensions	Maximum trim
Top	10 mm	0 mm
Bottom	10 mm	6 mm
Each side	10 mm	6 mm

Fitting and finishing

Please refer to door instruction manual for all fitting information. For identification, the Howdens logo, SKU code and batch number is on the top edge of the door.

The company has a policy of continuous product development and reserves the right to change any products and specifications at any time.

Dimensions								
Product code	Product height	Product width	Product thickness	Product weight	Building regulations	Stile	Top rail	Bottom rail
DFM7240 Regional UK	6'6" / 1981mm	2'3" / 686mm	44mm	24.703kg	E	110mm	110mm	180mm
DFM7260 Regional UK	6'6" / 1981mm	2'6" / 762mm	44mm	27.413kg	E	110mm	110mm	180mm
DFM7270 Regional UK	6'6" / 1981mm	2'9" / 838mm	44mm	29.203kg	ME	110mm	110mm	180mm

Key information

All sizes subject to standard industry tolerances

M = Part M - Mobility and access*

L = Part L - Warmth & insulation suitable for new build*

L = Part L - Warmth & insulation suitable for refurbishment projects*

E = Part E - Reduction of sound travel*

FD30/60/120 = Certified fire door*

F = Forest Stewardship Council (FSC®)*

P = Programme for the Endorsement of Forest Certification schemes (PEFC™)*

UK = UK Manufactured

† = Subject to availability

*Not applicable to all doors, please see the Dimensions table above for products that meet these standards