

Pre-finished Linear Smooth



Construction	
Construction	Moulded
Material core	Honeycomb paper
Country of origin	UK
Lock block height	360 mm
Lock block width	65 mm
Lock block position	Fitted centrally, to one side only - If the lock block is not indicated by the word 'LOCK' on the top edge, a hole will always be visible on the bottom edge on the side of the lock block.

Edging Information		
	Lipping dimensions	Maximum trim
Top	10 mm	6 mm
Bottom	10 mm	6 mm
Each side	10 mm	6 mm

The company has a policy of continuous product development and reserves the right to change any products and specifications at any time.

Dimensions								
Product code	Product height	Product width	Product thickness	Product weight	Building regulations	Stile	Top rail	Bottom rail
DIM7230 Regional UK	6'6" / 1981mm	2'0" / 610mm	35mm	10.053kg		110mm	110mm	180mm
DIM7240 Regional UK	6'6" / 1981mm	2'3" / 686mm	35mm	11.313kg		110mm	110mm	180mm
DIM7260 Regional UK	6'6" / 1981mm	2'6" / 762mm	35mm	12.563kg		110mm	110mm	180mm
DIM7270 Regional UK	6'6" / 1981mm	2'9" / 838mm	35mm	13.813kg	M	110mm	110mm	180mm

Key information

All sizes subject to standard industry tolerances

M = Part M - Mobility and access*

L = Part L - Warmth & insulation suitable for new build*

L = Part L - Warmth & insulation suitable for refurbishment projects*

E = Part E - Reduction of sound travel*

FD30/60/120 = Certified fire door*

F = Forest Stewardship Council (FSC®)*

P = Programme for the Endorsement of Forest Certification schemes (PEFC™)*

UK = UK Manufactured

† = Subject to availability

*Not applicable to all doors, please see the Dimensions table above for products that meet these standards