Pre-finished Middleweight Dordogne Smooth Door Kit





Aesthetics				
Colour	Satin White			
Door finish	Smooth			

Finishing Information					
Door lining finish	Primed and ready for painting				
Finish with	Paint				
Finising information	Faces fully finished edges require finishing				
Time saving	Saving 4 to 6 hours on finishing time				

Supplied With
1 x Door with female chrome hinge fitted
1 x Pre-machined primed lining with door stops
1 x Latch
3 x Male chrome hinges

Construction					
Construction material	MDF				
Construction	Moulded				
Door construction information	Semi-solid construction				
Fire rating	Not fire rated				
Moisture resistance	Not moisture resistant				

Edging Information				
	Lipping dimensions			
Bottom	10mm			
Each Side	10mm			
Lipping	Lipped on two long edges			



Dimensions										
Product code	Product height	Product width	Product thickness	Door weight	Building regulations	Approximate brick opening height	Approximate brick opening width	Lining size		
DPM9640	6'6" / 1981mm	2'3" / 686mm	35mm	12.163kg		2029mm	752mm	108mm		
DPM9641	6'6" / 1981mm	2'3" / 686mm	35mm	12.163kg		2029mm	752mm	132mm		
DPM9660	6'6" / 1981mm	2'6 / 762mm	35mm	13.263kg		2029mm	828mm	108mm		
DPM9661	6'6" / 1981mm	2'6 / 762mm	35mm	13.263kg		2029mm	828mm	132mm		
DPM9670	6'6" / 1981mm	2'9" / 838mm	35mm	14.363kg	M	2029mm	904mm	108mm		
DPM9671	6'6" / 1981mm	2'9" / 838mm	35mm	14.363kg	M	2029mm	904mm	132mm		

Key information

All sizes subject to standard industry tolerances

- M = Part M Mobility and access*
- L = Part L Warmth & insulation suitable for new build*
- L = Part L Warmth & insulation suitable for refurbishment projects*
- E = Part E Reduction of sound travel*

FD30/60/120 = Certified fire door*

- F = Forest Stewardship Council (FSC®)*
- P = Programme for the Endorsement of Forest Certification schemes (PEFC™)*
- **UK** = UK Manufactured
- t = Subject to availability

^{*}Not applicable to all doors, please see the Dimensions table above for products that meet these standards