

Pre-finished 6 Panel Grained Glazed Door



| Construction | |
|-------------------------|---|
| Construction | Softwood frame, butt jointed and stapled |
| Construction material | |
| Material core | Chipboard |
| Core material thickness | 28 mm |
| Country of origin | UK |
| Lock block height | 320 mm |
| Lock block width | 40 mm |
| Lock block position | Only on standard doors: Fitted centrally, to one side only - If the lock block is not indicated by the word 'LOCK' on the top edge, a hole will always be visible on the bottom edge on the side of the lock block. |
| Glazing fixing method | Beading and Pinned |
| Glazing stamp details | Howdens glazed doors do have Kite marks, however they are not legally required to be on every door. |
| Glazing style | Clear |

| Edging Information | | |
|--------------------|--------------------|--------------|
| | Lipping dimensions | Maximum trim |
| Top | 10 mm | 4 mm |
| Bottom | 10 mm | 4 mm |
| Each side | 10 mm | 4 mm |

Fitting and finishing

Please refer to door instructions for all fitting information.

This door can be rebated.

For identification, the Howdens logo, SKU code and batch number is on the top edge of the door.

Face fully finished

Supplied with toughened clear glass

Glazing certificate available



| Dimensions | | | | | | | |
|-----------------------|----------------|---------------|-------------------|----------------|----------------------|----------------|-------------------|
| Product code | Product height | Product width | Product thickness | Product weight | Building regulations | Glazing height | Glazing thickness |
| DGM1940 NEW UK | 6'6" / 1981mm | 2'3" / 686mm | 34.4mm | 17.51kg | | 984mm | 4mm |
| DGM1960 NEW UK | 6'6" / 1981mm | 2'6" / 762mm | 34.4mm | 19.44kg | | 984mm | 4mm |
| DGM1970 NEW UK | 6'6" / 1981mm | 2'9" / 838mm | 34.4mm | 21.37kg | M | 984mm | 4mm |

Key information

All sizes subject to standard industry tolerances

M = Part M - Mobility and access*

L = Part L - Warmth & insulation suitable for new build*

L = Part L - Warmth & insulation suitable for refurbishment projects*

E = Part E - Reduction of sound travel*

FD30/60/120 = Certified fire door*

F = Forest Stewardship Council (FSC®)*

P = Programme for the Endorsement of Forest Certification schemes (PEFC™)*

UK = UK Manufactured

† = Subject to availability

*Not applicable to all doors, please see the Dimensions table above for products that meet these standards

