

# Linear Oak Bi-fold Door



Construction	
Construction	Dowel and glue construction
Construction material	Veneered particleboard construction
Material core	Chipboard
Core material thickness	35mm
Veneer thickness	0.5 mm
Country of origin	Malaysia
Lock block additional information	A lock block is not included on this door as it is a solid construction. The lock can be fitted in any location on either side.

Edging Information		
	Lipping dimensions	Maximum trim
Top	10 mm	5 mm
Bottom	10 mm	5 mm
Each side	10 mm	5 mm
Edging additional information	An equal amount of timber should be removed from each side/ top & bottom. Remaining within the parameters of the maximum trim instructions ensures the construction of the door is not compromised.	

## Fitting and finishing

Please refer to door instructions for all fitting information.

For identification, the Howdens logo, SKU code and batch number is on the top edge of the door.

Hardwood doors can be finished with solvent based, oil based (not oil) or water based finishes.

All Howdens varnishes and stains are suitable for use with Howdens doors (Please always follow manufacturer's instructions).

This door is not suitable for waxes, polishes and/or oils (except Osmo Oil) as these products do not seal the door properly and may cause veneer delamination.



Dimensions						
Product code	Product height	Product width	Product thickness	Product weight	Top rail	Bottom rail
DIP1340	6'6" / 1981mm	2'3" / 686mm	35mm	31kg	110mm	180mm
DIP1360	6'6" / 1981mm	2'6" / 762mm	35mm	34kg	110mm	180mm

#### Key information

All sizes subject to standard industry tolerances

**M** = Part M - Mobility and access\*

**L** = Part L - Warmth & insulation suitable for new build\*

**L** = Part L - Warmth & insulation suitable for refurbishment projects\*

**E** = Part E - Reduction of sound travel\*

**FD30/60/120** = Certified fire door\*

**F** = Forest Stewardship Council (FSC®)\*

**P** = Programme for the Endorsement of Forest Certification schemes (PEFC™)\*

**UK** = UK Manufactured

**†** = Subject to availability

\*Not applicable to all doors, please see the Dimensions table above for products that meet these standards

