

# Primed Worcester fire doors



| Construction                      |   |
|-----------------------------------|---|
| Construction                      | Stub M&T or glue and dowel  |
| Construction material             | Particle board centre panel   |
| Country of origin                 | Various   |
| Lock block additional information | A lock block is not included on this door as it is a solid construction. The lock can be fitted in any location on either side. |

| Edging Information            |   |              |
|-------------------------------|---|--------------|
|                               | Lipping dimensions  | Maximum trim |
| Top                           | 10 mm   | 3 mm         |
| Bottom                        | 10 mm   | 3 mm         |
| Each side                     | 10 mm   | 3 mm         |
| Edging additional information | An equal amount of timber should be removed from each side & bottom. Remaining within the parameters of the maximum trim instructions ensures the construction of the door is not compromised and that the door when fitted complies with the fire certificate. |              |

## Fitting and finishing

Please refer to door instructions for all fitting information.  
For identification, the Howdens logo, SKU code and batch number is on the top edge of the door.  
All fire doors must be fitted in accordance with the fire certificate.  
Primed and ready for painting  
Fire certification available

| Dimensions   |                |               |                   |                |             |                      |             |
|--------------|----------------|---------------|-------------------|----------------|-------------|----------------------|-------------|
| Product code | Product height | Product width | Product thickness | Product weight | Fire rating | Building regulations | Bottom rail |
| DIF8440      | 6'6" / 1981mm  | 2'3" / 686mm  | 44mm              | 33kg           | <b>FD30</b> |                      | 175mm       |
| DIF8460      | 6'6" / 1981mm  | 2'6" / 762mm  | 44mm              | 36kg           | <b>FD30</b> |                      | 175mm       |
| DIF8470      | 6'6" / 1981mm  | 2'9" / 838mm  | 44mm              | 39kg           | <b>FD30</b> | <b>M</b>             | 175mm       |

#### Key information

All sizes subject to standard industry tolerances

**M** = Part M - Mobility and access\*

**L** = Part L - Warmth & insulation suitable for new build\*

**L** = Part L - Warmth & insulation suitable for refurbishment projects\*

**E** = Part E - Reduction of sound travel\*

**FD30/60/120** = Certified fire door\*

**F** = Forest Stewardship Council (FSC®)\*

**P** = Programme for the Endorsement of Forest Certification schemes (PEFC™)\*

**UK** = UK Manufactured

† = Subject to availability

\*Not applicable to all doors, please see the Dimensions table above for products that meet these standards