

Pre-finished Dordogne Smooth fire doors



Construction	
Construction material	Constructed using softwood timber stile and rail frame
Material core	Routed Flaxboard Core
Lock block additional information	A lock block is not included on this door as it is a solid construction. The lock can be fitted in any location on either side.

Edging Information		
	Lipping dimensions	Maximum trim
Edging additional information	An equal amount of timber should be removed from each side & bottom. Remaining within the parameters of the maximum trim instructions ensures the construction of the door is not compromised and that the door when fitted complies with the fire certificate.	

Fitting and finishing

Please refer to door instructions for all fitting information.
For identification, the Howdens logo, SKU code and batch number is on the top edge of the door.

All fire doors must be fitted in accordance with the fire certificate.

Face fully finished

Fire certification available



Dimensions									
Product code	Product height	Product width	Product thickness	Product weight	Fire rating	Building regulations	Stile	Top rail	Bottom rail
DFM1640 NEW UK	6'6" / 1981mm	2'3" / 686mm	44mm	27.35kg	FD30	E	120mm	117mm	185mm
DFM1660 NEW UK	6'6" / 1981mm	2'6" / 762mm	44mm	30.36kg	FD30	E	120mm	117mm	185mm
DFM1670 NEW UK	6'6" / 1981mm	2'9" / 838mm	44mm	34kg	FD30	E	120mm	117mm	185mm

Key information

All sizes subject to standard industry tolerances

M = Part M - Mobility and access*

L = Part L - Warmth & insulation suitable for new build*

L = Part L - Warmth & insulation suitable for refurbishment projects*

E = Part E - Reduction of sound travel*

FD30/60/120 = Certified fire door*

F = Forest Stewardship Council (FSC®)*

P = Programme for the Endorsement of Forest Certification schemes (PEFC™)*

UK = UK Manufactured

† = Subject to availability

*Not applicable to all doors, please see the Dimensions table above for products that meet these standards

