

Pre-finished Linear Oak



Construction	
Construction	Glue and dowel or slab
Construction material	Veneered particleboard construction
Material core	Particleboard
Veneer thickness	0.6 mm
Country of origin	USA
Lock block additional information	A lock block is not included on this door as it is a solid construction. The lock can be fitted in any location on either side.

Edging Information		
	Lipping dimensions	Maximum trim
Top	10 mm	5 mm
Bottom	10 mm	5 mm
Each side	10 mm	5 mm
Edging additional information	An equal amount of timber should be removed from each side/ top & bottom. Remaining within the parameters of the maximum trim instructions ensures the construction of the door is not compromised.	

Fitting and finishing

Please refer to door instructions for all fitting information.
For identification, the Howdens logo, SKU code and batch number is on the top edge of the door.
This door has a particleboard core which may be exposed if rebated. The use of the oak door pair maker is therefore recommended.
This door is not suitable for waxes, polishes and/or oils (except Osmo Oil) as these products do not seal the door properly and may cause veneer delamination.
Pre-finished with clear lacquer ready for installation;
Can save the builder up to 6 hours on finishing
This door can be finished using the following: Sadolin English Oak Stain and Sadolin Interior Varnish Satin
Any trimmed edges and all cut outs for hardware must be refinished.

Face fully finished

Dimensions								
Product code	Product height	Product width	Product thickness	Product weight	Building regulations	Stile	Top rail	Bottom rail
DIE7130	6'6" / 1981mm	2'0" / 610mm	35mm	28.624kg		110mm	110mm	180mm
DIE7140	6'6" / 1981mm	2'3" / 686mm	35mm	30.496kg		110mm	110mm	180mm
DIE7160	6'6" / 1981mm	2'6" / 762mm	35mm	34.785kg		110mm	110mm	180mm
DIE7170	6'6" / 1981mm	2'9" / 838mm	35mm	37.813kg	M	110mm	110mm	180mm

Key information

All sizes subject to standard industry tolerances

M = Part M - Mobility and access*

L = Part L - Warmth & insulation suitable for new build*

L = Part L - Warmth & insulation suitable for refurbishment projects*

E = Part E - Reduction of sound travel*

FD30/60/120 = Certified fire door*

F = Forest Stewardship Council (FSC®)*

P = Programme for the Endorsement of Forest Certification schemes (PEFC™)*

UK = UK Manufactured

† = Subject to availability

*Not applicable to all doors, please see the Dimensions table above for products that meet these standards