

Linear Oak Glazed



Construction	
Construction	Slab
Door construction information	Veneered particleboard
Material core	Particleboard
Veneer thickness	0.6 mm
Country of origin	USA
Lock block additional information	A lock block is not included on this door as it is a solid construction. The lock can be fitted in any location on either side.
Glazing fixing method	Beading and Pinned
Glazing stamp details	Howdens glazed doors do have Kite marks, however they are not legally required to be on every door.
Glazing style	Clear

Edging Information		
	Lipping dimensions	Maximum trim
Top	10 mm	4 mm
Bottom	10 mm	4 mm
Each side	10 mm	4 mm
Edging additional information	An equal amount of timber should be removed from each side/ top & bottom. Remaining within the parameters of the maximum trim instructions ensures the construction of the door is not compromised.	

Fitting and finishing

Please refer to door instructions for all fitting information. For identification, the Howdens logo, SKU code and batch number is on the top edge of the door.

This door has a particleboard core which may be exposed if rebated. The use of the oak door pair maker is therefore recommended.

This door is not suitable for waxes, polishes and/or oils (except Osmo Oil) as these products do not seal the door properly and may cause veneer delamination.

Supplied with toughened clear glass

Glazing certificate available

Dimensions										
Product code	Product height	Product width	Product thickness	Product weight	Building regulations	Top rail	Glazing height	Glazing width	Glazing thickness	Bottom rail
DIE2840	6'6" / 1981mm	2'3" / 686mm	35mm	28kg		110mm	1,473mm	204mm	5mm	180mm
DIE2860	6'6" / 1981mm	2'6" / 762mm	35mm	29.822kg		110mm	1,473mm	204mm	5mm	180mm
DIE2870	6'6" / 1981mm	2'9" / 838mm	35mm	32.822kg	M	110mm	1,473mm	204mm	5mm	180mm
DIE9240	2040mm	726mm	40mm	33.852kg		110mm	1,473mm	204mm	5mm	180mm
DIE9260	2040mm	826mm	40mm	38.852kg	M	110mm	1,473mm	204mm	5mm	180mm

Key information

All sizes subject to standard industry tolerances

M = Part M - Mobility and access*

L = Part L - Warmth & insulation suitable for new build*

L = Part L - Warmth & insulation suitable for refurbishment projects*

E = Part E - Reduction of sound travel*

FD30/60/120 = Certified fire door*

F = Forest Stewardship Council (FSC®)*

P = Programme for the Endorsement of Forest Certification schemes (PEFC™)*

UK = UK Manufactured

† = Subject to availability

*Not applicable to all doors, please see the Dimensions table above for products that meet these standards