

# Internal Softwood Door Linings

## Softwood Linings, Trenched

- Manufactured from premium quality softwood
- Ready for painting or staining
- Supplied unassembled with door stop
- Trenched to allow for easy head/jamb joint
- Reversible head adds an extra size to the lining



Dimensions				
To Fit Door Width	2'0" / 2'3"	2'0" / 2'3"	2'6" / 2'9"	2'6" / 2'9"
Nominal size of timber after machining (mm)	108 x 27.5	132 x 27.5	108 x 27.5	132 x 27.5
Product Code	DFR0004	DFR0005	DFR0014	DFR00015
Building Regulations	F	F	F	F
Thickness (mm)	108	132	108	132
Weights (kg)	8	9	8	8.9
A = Total Assembled Width (mm)	768	768	940	940
B = Total Assembled Height (mm)	2031.5	2031.5	2031.5	2031.5
C = Jamb Width (mm)	27.5	27.5	27.5	27.5
D = Head Height (mm)	27.5	27.5	27.5	27.5

All sizes subject to standard industry tolerances

Technical Specification	
Door Stop	Supplied unassembled
Trenched/Unrenched	Trenched
Intumescent Strip	N/A
Intumescent Strip Size (mm)	N/A
Core Material	Whitewood Spruce
Core Material Grade	Sawfalling
Construction	Solid
Moisture Content	14-18%
Fire Certificate	N/A
Veneer Spec	N/A
Veneer Source	N/A
Veneer Grade	N/A
Veneer Thickness (mm)	N/A

All Howdens softwood linings and casings may contain knots which will remain visible if a stain is used to finish the product

